



Canon imageFORMULA DR-C225 II ADF + Manuaalinen syöttöskanneri 600 x 600 DPI A4 musta

Tuotemerkki : Canon

Tuoteperhe: imageFORMULA

Tuotekoodi: 3258C003

Tuotteen nimi : DR-C225 II

Canon imageFORMULA DR-C225 II. Skannauksen enimmäiskoko: 216 x 356 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, ADF-skannausnopeus (mustavalkoinen, A4): 25 ppm. Skannerityyppi: ADF + Manuaalinen syöttöskanneri, Tuotteen väri: musta. Anturin tyyppi: CMOS CIS, Päivittäinen käyttöjako (maks.): 1500 sivua, Valonlähde: RGB LED. Suurin ISO A-luokan paperikoko: A4. Vakoliitännät: USB 2.0



Scanning		Power	
Maximum scan size *	216 x 356 mm	Power consumption (typical)	12.7 W
Optical scanning resolution *	600 x 600 DPI	Power consumption (off)	0.5 W
Colour scanning	✓	AC input frequency	50 - 60 Hz
Duplex scanning *	✓	Input voltage	100-240 V
ADF scan speed (b/w, A4)	25 ppm	Power consumption (sleep)	1.8 W
ADF scan speed (colour, A4)	25 ppm		
Duplex ADF scan speed (b/w, A4)	50 ipm	Weight & dimensions	
Duplex ADF scan speed (colour, A4)	50 ipm	Width	300 mm
		Depth	156 mm
		Height	220 mm
		Weight	2.8 kg
Design		Packaging content	
Scanner type *	ADF + Manual feed scanner	Cables included	AC, USB
Product colour *	Black	Quick start guide	✓
Built-in display *	✗	AC adapter included	✓
Performance		Sustainability	
Sensor type *	CMOS CIS	Sustainability certificates	ENERGY STAR
Light source	RGB LED		
Daily duty cycle (max) *	1500 pages	System requirements	
Scan drivers	ISIS, TWAIN	Windows operating systems supported	Windows 10, Windows 2000, Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Scanner error detection	✓	Mac operating systems supported	✓
Ultrasonic double sheet detection	✓	Mobile operating systems supported	Android, iOS
Paper handling		Operational conditions	
Maximum ISO A-series paper size *	A4	Operating temperature (T-T)	10 - 32.5 °C
		Operating relative humidity (H-H)	20 - 80%
Ports & interfaces		Other features	
USB port *	✓	Compliance certificates	RoHS
USB version	2.0	Logistics data	
Standard interfaces	USB 2.0	Harmonized System (HS) code	84716070
Power			
Power supply type *	AC		



4528472108384



5415247303954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.