Canon

Canon imageFORMULA DR-C225W II ADF + Manual feed scanner 600 x 600 DPI A4 Black

Brand : Canon

Product family: imageFORMULA Product code: 3259C003





Product name : DR-C225W II

Canon imageFORMULA DR-C225W II. Maximum scan size: 216 x 356 mm, Optical scanning resolution: 600 x 600 DPI, Output colour depth: 24 bit. Scanner type: ADF + Manual feed scanner, Product colour: Black. Sensor type: CMOS CIS, Daily duty cycle (max): 1500 pages, Light source: RGB LED. Maximum ISO A-series paper size: A4. Standard interfaces: USB 2.0, Wireless LAN

Scanning		Power	
Maximum scan size *	216 x 356 mm	Power supply type *	AC
Optical scanning resolution *	600 x 600 DPI	Power consumption (typical)	15.6 W
Colour scanning	✓	Power consumption (off)	0.5 W
Duplex scanning *	1	AC input frequency	50 - 60 Hz
Output colour depth	24 bit	Input voltage	100-240 V
Output greyscale depth	8 bit	Power consumption (sleep)	4.4 W
ADF scan speed (b/w, A4)	25 ppm	Weight & dimensions	
ADF scan speed (colour, A4)	25 ppm	Width	300 mm
Duplex ADF scan speed (b/w, A4)	50 ipm	Depth	156 mm
Duplex ADF scan speed (colour, A4)	50 ipm	Height	220 mm
Design		Weight	2.6 kg
Scanner type *	ADF + Manual feed scanner	Packaging content	
Product colour *	Black	Cables included	AC, USB
Built-in display *	×	Quick start guide	1
Performance		AC adapter included	✓
Sensor type *	CMOS CIS	Sustainability	
Light source	RGB LED 1500 pages	Sustainability certificates	ENERGY STAR
Daily duty cycle (max) *		System requirements	
Scan drivers	ISIS, TWAIN		Windows 10, Windows 2000,
Scanner error detection		Windows operating systems supported	Windows 7, Windows 8, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP
Ultrasonic double sheet detection	1		
Paper handling		Professional, Windows XP	
Maximum ISO A-series paper size *	A4		Professional x64
Ports & interfaces		Mac operating systems supported	1
USB port *	1	Mobile operating systems supported Android, iOS	
USB version	2.0	Operational conditions	
Standard interfaces	USB 2.0, Wireless LAN	Operating temperature (T-T)	10 - 32.5 °C
Network		Operating relative humidity (H-H)	20 - 80%
Wi-Fi	1	Other features	
		Compliance certificates	RoHS
		Logistics data	
		Harmonized System (HS) code	84716070



4528472108476

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.