

DELL Xeon Intel Silver 4210 processor 2.2 GHz 13.75 MB

Brand : DELL Product family: Xeon Product code: 338-BSDG

Product name: Intel Xeon

Silver 4210

Intel Xeon Silver 4210 2.20GHz, 10C/20T, 9.6GT/s, 13.75M Cache, Turbo, HT (85W)

DELL Xeon Intel Silver 4210 processor 2.2 GHz 13.75 MB:

The Intel Xeon® 4210 2.20GHz Ten Core Processor enhances the performance and the speed of your system. Additionally, the Virtualization Technology enables migration of more environments. It supports enhanced SpeedStep® technology that allows tradeoffs to be made between performance and power consumption.

Its Thermal Monitoring Technologies protect the processor package and the system from thermal failure through several thermal management features. The VT-x with Extended Page Tables (EPT) also known as Second Level Address Translation (SLAT), provides acceleration for memory intensive virtualized applications. Packed with more features, the Xeon 4210 2.20GHz Ten Core Processor is the ideal choice for virtually all of your data demanding or standard enterprise infrastructure applications.





| Processor | | Processor special features | |
|--|---|--|-----------|
| Processor generation Processor model * | 2nd Generation Intel® Xeon® Scalable 4210 | Intel Trusted Execution Technology Intel® Speed Shift Technology Intel VT-x with Extended Page | 4 |
| Processor base frequency * | 2.2 GHz | Tables (EPT) | ✓ |
| Processor family * | Intel Xeon Silver | Intel TSX-NI | ✓ |
| Processor cores * | 10 | Intel 64 | ✓ |
| Processor socket * | LGA 3647 (Socket P) | Intel Virtualization Technology (VT- | ✓ |
| Component for | Server/workstation | x) Intel Virtualization Technology for | |
| Processor lithography * | 14 nm | Directed I/O (VT-d) | ✓ |
| Processor threads | 20 | Intel Turbo Boost Max Technology | × |
| Processor operating modes * | 64-bit | 3.0 | ^ |
| Processor boost frequency | 3.2 GHz | AVX-512 Fused Multiply-Add (FMA) | 1 |
| Processor cache Thermal Design Power (TDP) | 13.75 MB 85 W | units Intel® Deep Learning Boost (Intel® | |
| Processor codename | Cascade Lake | DL Boost) on CPU | ✓ |
| Processor ARK ID | 193384 | Intel® Resource Director Technology (Intel® RDT) | ✓ |
| Memory | | Intel® Volume Management Device | 1 |
| Maximum internal memory supported by processor | 1.02 TB | (VMD) Intel® Run Sure Technology | × |
| Memory types supported by | DDR4-SDRAM | Mode-based Execute Control (MBE) | ✓ |
| processor | DDIG-SDIAM | Intel® vPro™ Platform Eligibility | ✓ |
| Memory clock speeds supported by processor | 2400 MHz | Intel Speed Select Technology (SST) | × |
| Memory channels * | Hexa-channel | Intel® Speed Select Technology - Base Frequency (Intel® SST-BF) | × |
| ECC | 1 | Intel® Optane™ DC Persistent | × |
| Graphics | | Memory technology | ^ |
| On-board graphics card * | × | Operational conditions | |
| Discrete graphics card * | × | Tcase | 78 °C |
| On-board graphics card model * | Not available | Technical details | |
| Discrete graphics card model * | Not available | Launch date | Q2'19 |
| Features | | Product type | Processor |
| Execute Disable Bit | ✓ | Status | Launched |
| Market segment | Server | Memory speed (max) | 2400 MHz |
| Maximum number of PCI Express lanes | 48 | Number of UPI links | 2 |
| PCI Express slots version | 3.0 | Logistics data | |
| Supported instruction sets | AVX-512 | Harmonized System (HS) code | 85423119 |

| Features | | Weight & dimensions | |
|--|-----|------------------------|---|
| Scalability | 2S | Processor package size | 76.0 x 56.5 mm |
| Embedded options available | 1 | Other features | |
| PCI Express CEM revision | 3.0 | | - PowerEdge R640 - PowerEdge R740 - PowerEdge R740XD - PowerEdge C6420 - PowerEdge R440 - PowerEdge T640 - PowerEdge T440 - PowerEdge FC640 - PowerEdge M640 - PowerEdge M640 VRTX - PowerEdge R540 - PowerEdge MX740c - PowerEdge R740xd2 - PowerEdge XR2 |
| Processor special features | | | |
| Intel® Hyper Threading Technology (Intel® HT Technology) | ✓ | Compatibility | |
| Intel® Turbo Boost Technology | 2.0 | | |
| Intel® AES New Instructions (Intel® AES-NI) | ✓ | | |
| Enhanced Intel SpeedStep Technology | ✓ | | |





5397184330098

0884116398691



884116398691

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.