Philips 43BDL3117P/00 computer monitor 109.2 cm (43") 3840 x 2160 pixels 4K Ultra HD LCD Black

Brand : Philips

Product code: 43BDL3117P/00

Product name : 43BDL3117P/00

43" (3840x2160), 750 cd/m², 220W, 100-240V, 13.94kg

Philips 43BDL3117P/00. Display diagonal: 109.2 cm (43"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0. VESA mounting. Product colour: Black

Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology *	109.2 cm (43") 3840 x 2160 pixels 4K Ultra HD 16:9 LCD	HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version DC-in jack	3 2.0 1 1.2
Backlight type	LED	Ergonomics	
Touchscreen *	×	VESA mounting *	1
Display brightness (typical)	750 cd/m ²	Panel mounting interface	200 x 200 mm
Screen shape * Supported graphics resolutions	Flat 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1440 x 900 (WXGA+), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	Power Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) *	G 86 kWh 80 W 0.5 W
Supported video modes	480p, 576p, 720p, 1080i, 1080p	Power consumption (max)	220 W
Contrast ratio (typical) *	1200:1	AC input voltage	100 - 240 V
Contrast ratio (dynamic)	500000:1	AC input frequency Energy efficiency scale	50 - 60 Hz A to G
Maximum refresh rate *	60 Hz	European Product Registry for	
Viewing angle, horizontal	178°	Energy Labelling (EPREL) code	1012835
Viewing angle, vertical Display number of colours *	178° 1.07 billion colours	Operational conditions	
Response time (fast)	8 ms	Operating temperature (T-T)	0 - 40 °C
Display diagonal (metric) Haze rate	108 cm 25%	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 60 °C 20 - 80%
		Operating relative humidity (H-H) Storage relative humidity (H-H)	20 - 80% 5 - 95%
Haze rate		Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	20 - 80%
Haze rate Performance	25%	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Weight & dimensions	20 - 80% 5 - 95% 0 - 3000 m
Haze rate Performance Operating hours (hours/days)	25%	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	20 - 80% 5 - 95%
Haze rate Performance Operating hours (hours/days) Multimedia Number of speakers RMS rated power	25% 24/7 2 10 W	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Weight & dimensions Width (without stand) Depth (without stand) Height (without stand)	20 - 80% 5 - 95% 0 - 3000 m 973 mm 76.8 mm 561.2 mm
Haze rate Performance Operating hours (hours/days) Multimedia Number of speakers RMS rated power Built-in speaker(s) *	25% 24/7 2 10 W	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Weight & dimensions Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	20 - 80% 5 - 95% 0 - 3000 m 973 mm 76.8 mm 561.2 mm
Haze rate Performance Operating hours (hours/days) Multimedia Number of speakers RMS rated power Built-in speaker(s) * Design Market positioning *	25% 24/7 2 10 W •	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Weight & dimensions Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Weight (without stand)	20 - 80% 5 - 95% 0 - 3000 m 973 mm 76.8 mm 561.2 mm 13.9 kg
Haze rate Performance Operating hours (hours/days) Multimedia Number of speakers RMS rated power Built-in speaker(s) * Design Market positioning * Product colour *	25% 24/7 2 10 W •	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Weight & dimensions Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Weight (without stand)	20 - 80% 5 - 95% 0 - 3000 m 973 mm 76.8 mm 561.2 mm 13.9 kg





8712581778712

0685417581382



685417581382

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.