

## Lexmark MS810de 1200 x 1200 DPI A4

**Tuotemerkki :** Lexmark

**Tuotekoodi:** 40G0161

**Tuotteen nimi :** MS810de

Lexmark MS810de. Tulostustekniikka: Laser. Värikasettien määrä: 1, Suurin toimintajakso: 250000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 52 ppm, Kaksipuolinen tulostus. Verkkovalmius. Tuotteen väri: musta, Harmaa



| Printing   |  | Network                                |  |
|--|--|--|--|
| Colour *   | ✗  | Supported network protocols (IPv4)     | TCP/IP IPv4, AppleTalk   |
| Print technology *                                       | Laser  | Supported network protocols (IPv6)     | TCP/IP IPv6, TCP, UDP  |
| Duplex printing *  | ✓  | Management protocols                   | HTTP, HTTPS (SSL*/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger |
| Maximum resolution *                                     | 1200 x 1200 DPI  |  |  |
| Print speed (black, normal quality, A4/US Letter) *      | 52 ppm   |  |  |
| Duplex print speed (black, normal quality, A4/US Letter) | 32 ppm   |  |  |
| Time to first page (black, normal)                       | 4.8 s  |  |  |
| Features   |  | Performance                            |  |
| Maximum duty cycle *                                     | 250000 pages per month                                     | Internal memory *                      | 512 MB   |
| Recommended duty cycle                                   | 3000 - 20000 pages per month                               | Maximum internal memory                | 2560 MB  |
| Printing colours *                                       | Black  | Processor frequency                    | 800 MHz  |
| Number of print cartridges *                             | 1  | Sound pressure level (printing)        | 57 dB  |
| Page description languages *                             | Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PostScript 3, PPDS  | Sound pressure level (duplex printing) | 56 dB  |
| Country of origin  | China  | Sound power level (standby)            | 32 dB  |
| Input & output capacity                                  |  | Design                                 |  |
| Total number of input trays *                            | 2  | Product colour *                       | Black, Grey  |
| Total input capacity *                                   | 650 sheets   |  |  |
| Total output capacity *                                  | 550 sheets   |  |  |
| Maximum number of input trays                            | 6  |  |  |
| Maximum input capacity                                   | 4400 sheets  |  |  |
| Maximum output capacity                                  | 2550 sheets  |  |  |
| Paper handling   |  |  |  |
| Maximum ISO A-series paper size *                        | A4   |  |  |
| Maximum print size                                       | 216 x 356 mm   |  |  |
| Paper tray media types *                                 | Card stock, Envelopes, Labels, Plain paper, Transparencies |  |  |
| ISO A-series sizes (A0...A9) *                           | A4, A5, A6   |  |  |
| Non-ISO print media sizes                                | Executive, Folio, Letter, Oficio, Statement, Legal         |  |  |
| JIS B-series sizes (B0...B9)                             | B5   |  |  |

| Paper handling                     |   | System requirements |  |
|------------------------------------|---|---------------------|--|
| Envelopes sizes                    | 7 3/4, 9, 10, B5, C5, DL                |                     | Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64 |
| Paper tray media weight            | 60 - 176 g/m <sup>2</sup>               |                     | Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion   |
| Paper tray media weight (imperial) | 7.26 - 21.3 kg (16 - 47 lbs)            |                     | Fedora 14, Fedora 15, RedHat EL Linux 4.0 U5, RedHat EL Linux 4.0 U6, RedHat EL Linux 4.0 U7, RedHat EL Linux 5.0, RedHat EL Linux 5.1, RedHat EL Linux 5.2, RedHat EL Linux 5.3, SuSE Linux 10, SuSE Linux 10.2, SuSE Linux 10.3, SuSE Linux 11   |
| Ports & interfaces                 |   |                     | Windows operating systems supported  |
| Standard interfaces                | Ethernet, USB 2.0                       |                     | Mac operating systems supported  |
| Direct printing *                  | ✓                                       |                     | Linux operating systems supported  |
| USB 2.0 ports quantity             | 3                                       |                     | Server operating systems supported   |
| Optional connectivity              | Parallel, Serial (RS-232), Wireless LAN |                     | Other operating systems supported  |
| Network                            |   |                     |  |
| Network ready                      | ✓                                       |                     |  |
| Wi-Fi *                            | ✗                                       |                     |  |
| Ethernet LAN *                     | ✓                                       |                     |  |
| Security algorithms                | 802.1x RADIUS, LEAP, MD5, PEAP          |                     |  |
| Operational conditions             |   |                     |  |
| Operating temperature (T-T)        |   | 16 - 32 °C          |  |
| Operating relative humidity (H-H)  |   | 8 - 80%             |  |
| Operating altitude                 |   | 0 - 2896 m          |  |
| Operating temperature (T-T)        |   | 60 - 90 °F          |  |
| Sustainability                     |   |                     |  |
| Sustainability certificates        |   | ENERGY STAR         |  |
| Weight & dimensions                |   |                     |  |
| Weight                             |   | 23.7 kg             |  |
| Dimensions (WxDxH)                 |   | 425 x 510 x 419 mm  |  |
| Packaging data                     |   |                     |  |
| Package weight                     |   | 27.5 kg             |  |
| Other features                     |   |                     |  |
| Mac compatibility                  |   | ✓                   |  |
| Networking features                |   | Gigabit Ethernet    |  |
| Power LED                          |   | ✓                   |  |
| Stand-by LED                       |   | ✓                   |  |
| Finishing option                   |   | ✓                   |  |
| Package dimensions (WxDxH)         |   | 615 x 537 x 563 mm  |  |



0734646423731



734646423731

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.