



35m Hybrid USB 3.2 Gen 2 Type A Cable

No.: 43357

35m USB 3.2 Gen 2 Extension with data transfer rates up to 10Gbps

Description

- 35m Hybrid USB 3.2 Gen 2 Cable combines the benefits of a copper and fibre optic cable
- Supports transfer rates up to 10Gbps
- USB Type A connection to computer and device
- Low RFI/EMI for sensitive environments
- 2 year warranty

The Lindy Hybrid USB 3.2 Cable extends a USB port by 35m, far longer than is possible with standard or active copper cables, whilst retaining SuperSpeed transfer rates of up to 10Gbps (backwards compatible with USB 2.0 devices). A lighter and more flexible construction makes this cable simple to install with cable trays and through conduits, whilst low RFI/EMI ensures that the cable can be installed in the most sensitive of environments.

This Hybrid Cable supports a variety of USB devices like storage media or webcams. It is fully compatible with, and can be used to extend signals from, 4K USB 3.2/3.1 webcams and video conferencing systems.

The screw-locking design of the USB Type A socket ensures a secure connection of the device.

For added convenience the Hybrid cable is bus-powered and features a USB Type A power cable, which can be attached to an external USB Power Supply (not included) should additional power be required.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Technical details

Connectors

- Connector A: USB Type A Male
- Connector B: USB Type A Female
- Power: USB Type A Male
- Housing Material: TPE
- Connector Plating: Stainless Steel C2650, Solder Nickel
- Pin Construction: Copper Alloy, Mating Area AU
- Pin Plating: Mating Area AU 1U

Dimensions (approx.) WxDxH:

USB A Male: 42.85x16x8mm [1.69x0.63x0.31in]

USB A Female: 43x28.4x7.12mm [1.69x1.12x0.28in]

Cable Construction

Length: 35m [114.83ft]

Standard: USB 3.2/3.1 Gen 2

Colour: Black

Type: Round

Jacket Diameter: 5.0mm [0.2in]

Jacket Material: PVC

Conductor Material: Tinned Copper Wire

Conductor Gauge: 26AWG [STP], 22AWG*2 [VBUS]

Shielding: AL

Specifications

Supported Bandwidth: 10Gbps

Nominal Attenuation: -

Minimum Bend Radius: 40mm [1.57in], static

Maximum Tensile Load: 500N [short term]

Operating Temperature: -20°C - 70°C [-4°F - 158°F]

Storage Temperature: -40°C - 85°C [-40°F - 185°F]

Transmission Medium: Optical Fiber

Transmission Technology: Optoelectronic Transmission

Miscellaneous

Packaging Type: Carton Box

Packaging Dimensions: 240x240x65mm [9.45x9.45x2.56in]

Net Weight: 1.35kg [2.98lb]

Gross Weight: 1.5kg [3.31lb]

Warranty (Years): 2

Product Compliance: CE, FCC, RoHS & REACH, CP 65

Package Contents

35m USB 3.2 Gen 2 Hybrid Cable with fixed 70cm USB Power Cable Type A

Lindy manual

Purchasing Information

No.: 43357

EAN: 4002888433570