



## DELL PowerEdge R760XS palvelin 960 GB Teline ( 2U ) Intel® Xeon® Gold 5416S 2 GHz 32 GB DDR5-SDRAM 1100 W

**Tuotemerkki :** DELL

**Tuoteperhe:** PowerEdge

**Tuotekoodi:** 62VFG

**Tuotteen nimi :** R760XS



DELL PowerEdge R760XS. Suoritinperhe: Intel® Xeon® Gold, Prosessorin taajuus: 2 GHz, Prosessorimalli: 5416S. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Kokonaistallennuskapasiteetti: 960 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline ( 2U )



Processor		Ports & interfaces	
Processor manufacturer *	Intel	Ethernet LAN (RJ-45) ports *	2
Processor family *	Intel® Xeon® Gold	USB 2.0 ports quantity	2
Processor model *	5416S	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Processor frequency *	2 GHz	VGA (D-Sub) ports quantity	2
Processor boost frequency	4 GHz	Power cables quantity	2
Processor cores	16		
Processor cache	30 MB		
Motherboard chipset	Intel C741		
Number of processors installed	1		
Thermal Design Power (TDP)	150 W		
Maximum internal memory supported by processor	512 GB		
Memory		Design	
Internal memory *	32 GB	Chassis type *	Rack (2U)
Internal memory type *	DDR5-SDRAM	Product colour	Black
Buffered memory type	Registered (buffered)	Rack rails	✓
Memory ranking	2	Bezel	✓
Memory slots	16x DIMM		
Memory layout (slots x size)	1 x 32 GB		
Memory data transfer rate	5600 MT/s		
Maximum internal memory *	1 TB		
Storage		Performance	
Total storage capacity *	960 GB	Remote administration	iDRAC9, Enterprise 16G
Number of SSDs installed	2		
SSD capacity	480 GB		
SSD interface	SATA III		
SSD size	2.5"		
Supported SSD sizes	3.5"		
		Software	
		Operating system installed *	✗
		Compatible operating systems *	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi
		Power	
		Redundant power supply (RPS) support *	✓
		Power supply *	1100 W
		Number of redundant power supplies supported	2
		Number of redundant power supplies installed	2
		Power supply input voltage	100 - 240 V

Storage		Power	
Number of SSDs supported	8	Power cable length	2 m
RAID support *	✓	Power cable connector 1	C13 coupler
Supported RAID controllers	PERC H755	Power cable connector 2	C14 coupler
Hot-Plug support	✓	Power cable current	12 A
Optical drive type *	✗	Operational conditions	
Internal drive bays	8	Storage temperature (T-T)	-40 - 65 °C
Supported storage drive interfaces	SAS, Serial ATA	Storage relative humidity (H-H)	5 - 95%
Storage drive adapter included	✓	Operating altitude	0 - 3048 m
Storage drive adapter type	2.5" - 3.5"	Non-operating altitude	0 - 12000 m
Network		Weight & dimensions	
Ethernet LAN	✓	Width	482 mm
Cabling technology	10/100/1000Base-T(X)	Height	86.8 mm
Ethernet interface type	Gigabit Ethernet	Weight	28.6 kg
		Other features	
		Data transfer rate	6 Gbit/s
		Bytes per sector	512



5397184843529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date