



DELL PowerEdge R760XS server 480 GB Rack (2U) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 1100 W

Brand : DELL

Product family: PowerEdge

Product code: 0C17J

Product name : R760XS



- No OS

- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)

- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD

- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN, PERC H755, iDRAC9, Enterprise 16G, 2 x 1100W, No OS

[DELL PowerEdge R760XS server 480 GB Rack \(2U\) Intel Xeon Silver 4410Y 2 GHz 32 GB DDR5-SDRAM 1100 W:](#)



The perfect blend of performance and density

Run the most popular IT applications with ease thanks to the balanced compute and flexible storage of this air-cooled server.

DELL PowerEdge R760XS. Processor family: Intel Xeon Silver, Processor frequency: 2 GHz, Processor model: 4410Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout (slots x size): 1 x 32 GB. Total storage capacity: 480 GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 1100 W, Redundant power supply (RPS) support. Chassis type: Rack (2U)

Processor		Network	
Processor manufacturer *	Intel	Ethernet LAN	✓
Processor family *	Intel Xeon Silver	Cabling technology	10/100/1000Base-T(X)
Processor model *	4410Y	Ethernet interface type	Gigabit Ethernet
Processor frequency *	2 GHz	Ports & interfaces	
Processor boost frequency	3.9 GHz	Ethernet LAN (RJ-45) ports *	2
Processor cores	12	USB 2.0 ports quantity	2
Processor cache	30 MB	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Motherboard chipset	Intel C741	VGA (D-Sub) ports quantity	2
Number of processors installed	1	Design	
Thermal Design Power (TDP)	150 W	Chassis type *	Rack (2U)
Maximum internal memory supported by processor	512 GB	Product colour	Black
Memory types supported by processor	DDR5-SDRAM	Rack rails	✓
Memory clock speeds supported by processor	4000 MHz	Bezel	✓
Memory		Performance	
Internal memory *	32 GB	Remote administration	iDRAC9, Enterprise 16G
Internal memory type *	DDR5-SDRAM	Software	
Buffered memory type	Registered (buffered)	Operating system installed *	✗
Memory ranking	2	Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi	
Memory slots	16x DIMM	Compatible operating systems *	
Memory layout (slots x size)	1 x 32 GB	Power	
Memory data transfer rate	5600 MT/s	Redundant power supply (RPS) support *	✓
Maximum internal memory *	1 TB	Power supply *	1100 W
Storage			
Total storage capacity *	480 GB		
Number of SSDs installed	1		
SSD capacity	480 GB		

Storage		Power	
SSD interface	SATA III	Number of redundant power supplies supported	2
SSD size	2.5"	Number of redundant power supplies installed	2
Supported SSD sizes	3.5"	Power supply input voltage	100 - 240 V
Number of SSDs supported	8	Power cable length	2 m
RAID support *	✓	Power cable connector 1	C13 coupler
Supported RAID controllers	PERC H755	Power cable connector 2	C14 coupler
Hot-Plug support	✓	Power cable current	12 A
Internal drive bays	8	Operational conditions	
Supported storage drive interfaces	SAS, Serial ATA	Storage temperature (T-T)	-40 - 65 °C
Drive writes per day (DWPD)	1	Storage relative humidity (H-H)	5 - 95%
Storage drive adapter included	✓	Operating altitude	0 - 3048 m
Storage drive adapter type	2.5" - 3.5"	Non-operating altitude	0 - 12000 m
Graphics		Weight & dimensions	
On-board graphics card	✗	Width	482 mm
On-board graphics card model	Not available	Height	86.8 mm
		Weight	28.6 kg
		Other features	
		Data transfer rate	6 Gbit/s
		Bytes per sector	512



5397184843505

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-NOV-2024. Prints or copies of Information are only valid on the printed Publication date