

## DELL PowerEdge R760XS server 480 GB Rack (2U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 1100 W

Brand : DELL Product family: PowerEdge Product code: 8R4YN

**Product name: R760XS** 




- No O
- Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz)
- 32GB DDR5-SDRAM (1 x 32) & 480GB SSD
- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410T (26.25MB Cache, 2.7GHz), 32GB DDR5-SDRAM, 480GB SSD, LAN, PERC H755, iDRAC9, Enterprise 16G, 2  $\times$  1100W, No OS

DELL PowerEdge R760XS server 480 GB Rack (2U) Intel Xeon Silver 4410T 2.7 GHz 32 GB DDR5-SDRAM 1100 W:

## The perfect blend of performance and density

Run the most popular IT applications with ease thanks to the balanced compute and flexible storage of this air-cooled server.





Processor		Network	
Processor manufacturer * Processor family * Processor model *	Intel Xeon Silver 4410T  7 * 2.7 GHz quency 4 GHz 10 26.25 MB t Intel C741	Ethernet LAN Cabling technology Ethernet interface type	✓ 10/100/1000Base-T(X) Gigabit Ethernet
Processor frequency * Processor boost frequency Processor cores Processor cache Motherboard chipset Number of processors installed		Ports & interfaces  Ethernet LAN (RJ-45) ports *  USB 2.0 ports quantity  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity  VGA (D-Sub) ports quantity	2 2 1 2
Thermal Design Power (TDP)  Maximum internal memory supported by processor  Memory types supported by processor	150 W 512 GB DDR5-SDRAM	Design Chassis type * Product colour	Rack (2U) Black
Memory clock speeds supported by processor	4000 MHz	Rack rails Bezel	<b>/</b>
Memory Internal memory * Internal memory type *	32 GB DDR5-SDRAM Registered (buffered) 2 16x DIMM 1 x 32 GB 5600 MT/s 1 TB	Performance Remote administration Software	iDRAC9, Enterprise 16G
Buffered memory type Memory ranking Memory slots Memory layout (slots x size) Memory data transfer rate Maximum internal memory *		Operating system installed *  Compatible operating systems *	X Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware vSAN/ESXi
Storage		Power	
Total storage capacity * Number of SSDs installed SSD capacity	480 GB 1 480 GB	Redundant power supply (RPS) support * Power supply *	7 1100 W

Storage		Power	
SSD interface SSD size	SATA III 2.5"	Number of redundant power supplies supported	2
Supported SSD sizes 3.5"  Number of SSDs supported 8  RAID support *   ✓  Supported RAID controllers PERC H755  Hot-Plug support  ✓ Internal drive bays 8	3.5" 8  PERC H755  SAS, Serial ATA	Number of redundant power supplies installed Power supply input voltage Power cable length Power cable connector 1 Power cable connector 2 Power cable current  Operational conditions	2 100 - 240 V 2 m C13 coupler C14 coupler 12 A
		Storage temperature (T-T) Storage relative humidity (H-H) Operating altitude	-40 - 65 °C 5 - 95% 0 - 3048 m
Graphics		Non-operating altitude	0 - 12000 m
On-board graphics card On-board graphics card model	X Not available	Weight & dimensions Width	482 mm
		Height Weight	86.8 mm 28.6 kg
		Other features	
		Data transfer rate Bytes per sector	6 Gbit/s 512



5397184843512

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.