## Lenovo ThinkSystem ST650 V2 server Tower (4U) Intel Xeon Silver 4314 2.4 GHz 32 GB DDR4-SDRAM 750 W

Brand: Lenovo Product family: ThinkSystem Product code: 7Z74A033EA

Product name: ST650 V2

- No OS
- Intel Xeon Silver 4314 (24MB Cache, 2.4GHz)
- 32GB (3200MHz) DDR4-SDRAM (1 x 32)

Intel Xeon Silver 4314 (24MB Cache,  $2.4 \mathrm{GHz}$ ), 32GB DDR4-SDRAM (3200MHz), LAN (Broadcom 57416), 9350-8i, 750W, No OS

Lenovo ThinkSystem ST650 V2. Processor family: Intel Xeon Silver, Processor frequency: 2.4 GHz, Processor model: 4314. Internal memory: 32 GB, Internal memory type: DDR4-SDRAM, Memory layout (slots x size):  $1 \times 32$  GB. Ethernet LAN, Cabling technology: 10/100/1000Base-T(X). Power supply: 750 W, Redundant power supply (RPS) support. Chassis type: Tower (4U)



Processor		Design	
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency	Intel Intel Xeon Silver 4314 2.4 GHz 3.4 GHz	Chassis type * Product colour Rack mounting	Tower (4U) Black
		Performance	
Processor cache Number of processors installed	24 MB 1	Performance management Trusted Platform Module (TPM)	XClarity Enterprise  ✓
Memory		Trusted Platform Module (TPM) version	2.0
Internal memory * Internal memory type *	32 GB DDR4-SDRAM	Software	
Memory clock speed	3200 MHz	Operating system installed *	×
Memory layout (slots x size)  Storage	1 x 32 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
RAID support *	<b>✓</b>	Power	
RAID levels Supported RAID controllers	0, 1, 5, 6, 10, 50, 60 9350-8i	Redundant power supply (RPS) support *	<b>✓</b>
Internal drive bays	8	Power supply *	750 W
Graphics		Number of redundant power supplies installed	1
Maximum graphics card memory	16 MB	Operational conditions	
Network  LAN controller  Ethernet LAN  Cabling technology  Ethernet interface type	Broadcom 57416  ✓ 10/100/1000Base-T(X) 10 Gigabit Ethernet	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	5 - 45 °C -40 - 60 °C 8 - 90% 8 - 90% 0 - 3050 m
Ports & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity VGA (D-Sub) ports quantity Serial ports quantity	3 1 5 1	Width Depth Height	175 mm 734 mm 462 mm

