Lenovo ThinkSystem ST50 V2 server 2 TB Tower Intel Xeon E E-2324G 3.1 GHz 16 GB DDR4-SDRAM 500 W

Brand : Lenovo Product family: ThinkSystem Product code: 7D8JA045EA

Product name: ST50 V2

- No OS
- Intel Xeon E-2324G (8MB Cache, 3.1GHz)
- 16GB DDR4-SDRAM (1 x 16) & 2000GB HDD

Intel Xeon E-2324G (8MB Cache, 3.1GHz), 16GB DDR4-SDRAM, 2000GB HDD, Intel UHD Graphics P750, LAN (Intel I219-LM), 500W, No OS

Lenovo ThinkSystem ST50 V2 server 2 TB Tower Intel Xeon E E-2324G 3.1 GHz 16 GB DDR4-SDRAM 500 W:

The Lenovo ThinkSystem ST50 V2 single-socket tower server is an entry level server ideal for small businesses, home offices, retail, educational institutions and branch offices. The server is based on the Intel Xeon E-2300 Series processors, formerly codenamed "Rocket Lake".

This product guide provides essential presales information to understand the ThinkSystem ST50 V2 server, its key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the ST50 V2 and consider its use in IT solutions.





| Processor | | Ports & interfaces | | | | | | |
|---|--|--|--|--|--|--|--|--|
| Processor manufacturer * Processor family * Processor model * Processor frequency * Processor boost frequency | Intel Intel Xeon E E-2324G 3.1 GHz 4.6 GHz | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity VGA (D-Sub) ports quantity Serial ports quantity DisplayPorts quantity | 1 1 1 2 | | | | | |
| Processor cache | 8 MB | Design | | | | | | |
| Motherboard chipset Number of processors installed | Intel C256 1 | Chassis type * Product colour | Tower Black | | | | | |
| Memory | | Performance | | | | | | |
| Internal memory * Internal memory type * Memory slots ECC | 16 GB DDR4-SDRAM 4x DIMM ✓ | BIOS type Trusted Platform Module (TPM) Trusted Platform Module (TPM) version | UEFI ✓ 2.0 | | | | | |
| Memory layout (slots x size) | 1 x 16 GB | Software | | | | | | |
| Maximum internal memory * | 128 GB | Operating system installed * | × | | | | | |
| Storage Total storage capacity * | 2 TD | Compatible operating systems * | Microsoft Windows Server, Red Hat Enterprise Linux, VMware ESXi | | | | | |
| Number of HDDs installed HDD capacity | per of HDDs installed 2 | | Processor special features | | | | | |
| Graphics | | CPU configuration (max) 1 Power | | | | | | |
| On-board graphics card On-board graphics card model Network | ✓ Intel UHD Graphics P750 | Redundant power supply (RPS) support * Power supply * | × 500 W | | | | | |
| LAN controller | Intel® I219-LM | Operational conditions | | | | | | |
| Ethernet LAN Cabling technology Ethernet interface type | 10/100/1000Base-T(X) Gigabit Ethernet | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 5 - 45 °C -40 - 60 °C 8 - 90% 8 - 90% 0 - 3050 m | | | | | |
| Ports & interfaces | | Operating altitude | | | | | | |
| Ethernet LAN (RJ-45) ports * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 6 | Weight & dimensions Width | 170 mm | | | | | |
| USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity | 2 | Depth | 316 mm | | | | | |

| | | | | | | _ | | | | | | | | |
|---|---|----------|---|---|----|----|---|----|----|---|----|---|---|---|
| v | v | Δ | 1 | n | ٠, | ۸. | М | ın | ne | n | CI | 1 | n | _ |
| | | | | | | | | | | | | | | |

Height 376 mm Weight 9.4 kg

