

Lenovo

Lenovo ThinkSystem ST50 V2 palvelin 2 TB Tower Intel Xeon E E-2324G 3,1 GHz 16 GB DDR4-SDRAM 500 W

Tuotemerkki : Lenovo**Tuoteperhe**: ThinkSystem**Tuotekoodi**: 7D8JA045EA**Tuotteen nimi** : ST50 V2

Lenovo ThinkSystem ST50 V2. Suoritinperhe: Intel Xeon E, Prosessorin taajuus: 3,1 GHz, Prosessorimalli: E-2324G. Sisäinen muisti: 16 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 16 GB. Kokonaistallennuskapasiteetti: 2 TB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 500 W. Alustatyyppi: Tower

Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
Processor family *	Intel Xeon E	VGA (D-Sub) ports quantity	1
Processor model *	E-2324G	Serial ports quantity	1
Processor frequency *	3.1 GHz	DisplayPorts quantity	2
Processor boost frequency	4.6 GHz	Design	
Processor cache	8 MB	Chassis type *	Tower
Motherboard chipset	Intel C256	Product colour	Black
Number of processors installed	1	Performance	
Memory		BIOS type	UEFI
Internal memory *	16 GB	Trusted Platform Module (TPM)	✓
Internal memory type *	DDR4-SDRAM	Trusted Platform Module (TPM) version	2.0
Memory slots	4x DIMM	Software	
ECC	✓	Operating system installed *	✗
Memory layout (slots x size)	1 x 16 GB	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, VMware ESXi
Maximum internal memory *	128 GB	Processor special features	
Storage		CPU configuration (max)	1
Total storage capacity *	2 TB	Power	
Number of HDDs installed	2	Redundant power supply (RPS) support *	✗
HDD capacity	1 TB	Power supply *	500 W
Graphics		Operational conditions	
On-board graphics card	✓	Operating temperature (T-T)	5 - 45 °C
On-board graphics card model	Intel UHD Graphics P750	Storage temperature (T-T)	-40 - 60 °C
Network		Operating relative humidity (H-H)	8 - 90%
LAN controller	Intel® I219-LM	Storage relative humidity (H-H)	8 - 90%
Ethernet LAN	✓	Operating altitude	0 - 3050 m
Cabling technology	10/100/1000Base-T(X)	Weight & dimensions	
Ethernet interface type	Gigabit Ethernet	Width	170 mm
Ports & interfaces		Depth	316 mm
Ethernet LAN (RJ-45) ports *	1	Height	376 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	6	Weight	9.4 kg
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-DEC-2024. Prints or copies of Information are only valid on the printed Publication date