



Lenovo ThinkSystem SR630 V3 server Rack (1U) Intel Xeon Silver 4509Y 2.6 GHz 32 GB DDR5-SDRAM 1100 W



Brand : Lenovo

Product family: ThinkSystem

Product code: 7D73A047EA

Product name : SR630 V3

- Intel Xeon Silver 4509Y (22.5MB Cache, 2.6GHz)
- 32GB (5600MHz) DDR5-SDRAM (1 x 32)

Intel Xeon Silver 4509Y (22.5MB Cache, 2.6GHz), 32GB DDR5-SDRAM (5600MHz), 9350-8i, 1100W
Lenovo ThinkSystem SR630 V3. Processor family: Intel Xeon Silver, Processor frequency: 2.6 GHz,
Processor model: 4509Y. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM, Memory layout
(slots x size): 1 x 32 GB. Power supply: 1100 W, Redundant power supply (RPS) support. Chassis type:
Rack (1U)

Processor		Graphics	
Processor manufacturer *	Intel	Maximum graphics card memory	16 MB
Processor family *	Intel Xeon Silver	Ports & interfaces	
Processor model *	4509Y	Ethernet LAN (RJ-45) ports *	1
Processor frequency *	2.6 GHz	USB 2.0 ports quantity	2
Processor boost frequency	4.1 GHz	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Processor cores	8	VGA (D-Sub) ports quantity	1
Processor cache	22.5 MB	Design	
Number of processors installed	1	Chassis type *	Rack (1U)
Maximum number of SMP processors	2	Performance	
Memory		Performance management	XClarity Controller Platinum
Internal memory *	32 GB	Trusted Platform Module (TPM)	✓
Internal memory type *	DDR5-SDRAM	Trusted Platform Module (TPM) version	2.0
Memory slots	32x DIMM	Software	
ECC	✓	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi, Ubuntu Server
Memory clock speed	5600 MHz	Power	
Memory layout (slots x size)	1 x 32 GB	Redundant power supply (RPS) support *	✓
Maximum internal memory *	8.19 TB	Power supply *	1100 W
Storage		Number of redundant power supplies supported	2
RAID support *	✓	Weight & dimensions	
RAID levels	0, 1, 5, 6, 10, 50, 60	Width	440 mm
Supported RAID controllers	9350-8i	Depth	773 mm
Hot-swap	✓	Height	43 mm
Optical drive type *	✗	Technical details	
Internal drive bays	8	2.5" HDD support	8
Supported storage drive interfaces	SAS		
Graphics			
On-board graphics card	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date