NETGEAR GS108LP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta, Harmaa

Tuotemerkki : NETGEAR Tuotekoodi: GS108LP-100EUS

WOOTHING THE TOLE WATER

NETGEAR GS108LP. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000). MAC-osoitetaulukko: 4000 entries, Kytkentäkapasiteetti: 16 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE.... DC-syöttöjännite: 54 V. Virtaliitin: AC-in-liitin. Power over Ethernet -tuki.

Seinäkiinnitteinen, Telineasennus, Kotelo: 1U

Tuotteen nimi: GS108LP





Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	2752476 h
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	DC input voltage	54 V
type * Gigabit Ethernet (copper) ports		Input current Power consumption (typical)	1.25 A 67.5 W
quantity	8	Power consumption (typical)	130 W
Power connector	AC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	1
	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE	Power over Ethernet plus (PoE+)	
Networking standards *	802.3at, IEEE 802.3az, IEEE 802.3i,	ports quantity	8
100	IEEE 802.3u, IEEE 802.3x	Total Power over Ethernet (PoE) budget	60 W
10G support *	×	Operational conditions	
Flow control support Ethernet LAN data rates	10,100,1000 Mbit/s	Operating temperature (T-T)	0 - 40 °C
Data transmission	10,100,1000 Mbigs	Storage temperature (T-T)	-20 - 70 °C
Switching capacity *	16 Gbit/s	Operating relative humidity (H-H)	0 - 90%
MAC address table *	4000 entries	Storage relative humidity (H-H)	0 - 95%
Store-and-forward	✓	Operating altitude	0 - 1000 m 230.85 BTU/h
Jumbo frames support	✓	Heat dissipation	230.83 610/11
Packet forwarding	✓	Weight & dimensions	226
Design		Width Depth	236 mm 102 mm
Rack mounting *	/	Height	27 mm
Form factor	1U	Weight	600 g
Product colour	Black, Grey	Logistics data	
LED indicators	✓	Harmonized System (HS) code	85176990
Wall mountable	✓		
Number of fans	0 fan(s)		
Performance			
Buffer size	192 KB		
Plug and Play	✓		





606449134971

0606449134971

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.