

## NETGEAR GS724TP-300EUS verkkokytkin Hallittu L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Sininen

**Tuotemerkki :** NETGEAR

**Tuotekoodi:** GS724TP-300EUS

**Tuotteen nimi :** GS724TP-300EUS



NETGEAR GS724TP-300EUS. Kytin tyyppi: Hallittu, Kytinkerros: L2/L3/L4. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 52 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE.... Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Telineasennus

|   |  |  |                       |
|---|--|--|-----------------------|
| <b>Management features</b>                      |  | <b>Multicast features</b>              |                       |
| Switch type *                                   | Managed  | Multicast support                      | ✓                     |
| Switch layer                                    | L2/L3/L4   | Number of multicast groups filtered    | 128                   |
| Quality of Service (QoS) support                | ✓  | <b>Protocols</b>                       |                       |
| Web-based management                            | ✓  | Management protocols                   | SNMP v1/v2/v3         |
| System event log                                | ✓  | <b>Design</b>                          |                       |
| <b>Ports &amp; interfaces</b>                   |  | Rack mounting *                        | ✓                     |
| Basic switching RJ-45 Ethernet ports quantity * | 24   | Stackable *                            | ✓                     |
| Basic switching RJ-45 Ethernet ports type *     | Gigabit Ethernet (10/100/1000)   | Product colour                         | Blue                  |
| SFP module slots quantity                       | 2  | LED indicators                         | Activity, Link, Speed |
| Power connector                                 | DC-in jack   | Number of fans                         | 3 fan(s)              |
| <b>Network</b>                                  |  | <b>Performance</b>                     |                       |
| Networking standards *                          | IEEE 802.1D, IEEE 802.1ab, IEEE 802.1as, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3x, IEEE 802.3z | Noise level                            | 0 dB                  |
| 10G support *                                   | ✓  | Firmware upgradeable                   | ✓                     |
| Copper ethernet cabling technology              | 10BASE-T, 100BASE-T, 100BASE-TX, 1000BASE-T  | Mean time between failures (MTBF)      | 634966 h              |
| Port mirroring                                  | ✓  | <b>Power</b>                           |                       |
| Full duplex                                     | ✓  | Power supply included *                | ✓                     |
| IP routing                                      | ✓  | AC input voltage                       | 100 - 240 V           |
| Flow control support                            | ✓  | Power consumption (max)                | 446.7 W               |
| Link aggregation                                | ✓  | <b>Power over Ethernet (PoE)</b>       |                       |
| Broadcast storm control                         | ✓  | Power over Ethernet (PoE) *            | ✓                     |
| Spanning tree protocol                          | ✓  | Total Power over Ethernet (PoE) budget | 380 W                 |
| VLAN support                                    | ✓  | <b>Operational conditions</b>          |                       |
| Number of VLANs                                 | 64   | Operating temperature (T-T)            | 0 - 50 °C             |
| <b>Optical fiber</b>                            |  | Storage temperature (T-T)              | -20 - 70 °C           |
| Fiber ethernet cabling technology               | 1000BASE-LX, 1000BASE-SX   | Operating relative humidity (H-H)      | 0 - 90%               |
| <b>Data transmission</b>                        |  | Storage relative humidity (H-H)        | 0 - 95%               |
| Switching capacity *                            | 52 Gbit/s  | Operating altitude                     | 0 - 3000 m            |
|   |  | <b>Weight &amp; dimensions</b>         |                       |
|   |  | Width                                  | 440 mm                |
|   |  | Depth                                  | 204 mm                |

| Data transmission         |                               | Weight & dimensions |  |
|---------------------------|-------------------------------|---------------------|--|
| MAC address table *       | 8000 entries                  | Height              | 43 mm  |
| Store-and-forward         | ✓                             | Weight              | 3.7 kg   |
| Number of queues          | 8                             | Packaging content   |  |
| Number of static routes   | 32                            | Cables included     | AC   |
| Jumbo frames support      | ✓                             | Quick start guide   | ✓  |
| Jumbo frames              | 9216                          | User guide          | ✓  |
| Packet buffer memory      | 0.512 MB                      | Manual              | ✓  |
| Security                  |                               | Certificates        |  |
| DHCP features             | DHCP client                   | Certification       | CE, FCC, VCCI, EN, C-Tick, CCC, CSA, UL/cUL, IEC |
| Access Control List (ACL) | ✓                             |                     |  |
| IGMP snooping             | ✓                             |                     |  |
| Security algorithms       | 802.1x RADIUS, HTTPS, SSL/TLS |                     |  |
| MAC address filtering     | ✓                             |                     |  |
| SSH/SSL support           | ✓                             |                     |  |



0606449162660



606449162660



(01)10606449162667

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.