

## NETGEAR GS324P Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

**Tuotemerkki :** NETGEAR

**Tuotekoodi:** GS324P-100EUS

**Tuotteen nimi :** GS324P

NETGEAR GS324P. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3at. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	1193574 h
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports quantity *	24	AC input frequency	50 - 60 Hz
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Input current	3 A
Network		Power consumption (max)	210 W
Networking standards *	IEEE 802.1p, IEEE 802.3at	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Full duplex	✓	Power over Ethernet plus (PoE+) ports quantity	16
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) power per port	30 W
Auto-negotiation	✓	Total Power over Ethernet (PoE) budget	190 W
Data transmission		Operational conditions	
Switching capacity *	48 Gbit/s	Operating temperature (T-T)	0 - 45 °C
MAC address table *	8000 entries	Storage temperature (T-T)	-20 - 70 °C
Latency (1 Gbps)	4 µs	Operating relative humidity (H-H)	10 - 90%
Jumbo frames support	✓	Storage relative humidity (H-H)	10 - 95%
Jumbo frames	10000	Operating altitude	0 - 3000 m
Packet forwarding rate (1 Gbps)	1448000 pps	Heat dissipation	718.2 BTU/h
Packet buffer memory	0.192 MB	Weight & dimensions	
Security		Width	330 mm
Queue scheduling algorithms	Weighted Round Robin (WRR)	Depth	206 mm
Design		Height	43 mm
Rack mounting *	✓	Weight	2.44 kg
Form factor	1U	Certificates	
Product colour	Black	Certification	CB, CE LVD, UL
Housing material	Metal	Logistics data	
LED indicators	Activity, Link, PoE, Power, Speed	Harmonized System (HS) code	85176990
Number of fans	1 fan(s)		
Electromagnetic compatibility	CE, FCC 15 A, IC A, RCM, VCCI, KC		



0606449144802



606449144802

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.