

NETGEAR GS524UP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa

Tuotemerkki : NETGEAR

Tuotekoodi: GS524UP-100EUS

Tuotteen nimi : GS524UP

NETGEAR GS524UP. Kytkein tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 48 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3p, IEEE.... Power over Ethernet -tuki. Telineasennus

Management features		Power	
Switch type *	Unmanaged	Power supply included *	✓
Quality of Service (QoS) support	✓	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50 - 60 Hz
Basic switching RJ-45 Ethernet ports quantity *	24	Input current	8 - 4 A
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power consumption (max)	578.8 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u	Power over Ethernet (PoE) *	✓
10G support *	✗	Power over Ethernet (PoE) type supported	PoE+
Full duplex	✓	Power over Ethernet plus (PoE+) ports quantity	24
Half duplex	✓	Power over Ethernet (PoE) power per port	60 W
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	480 W
Data transmission		Operational conditions	
Switching capacity *	48 Gbit/s	Operating temperature (T-T)	0 - 50 °C
MAC address table *	8000 entries	Storage temperature (T-T)	-20 - 70 °C
Latency (1 Gbps)	12 µs	Operating relative humidity (H-H)	10 - 90%
Packet forwarding rate (1 Gbps)	1448000 pps	Operating altitude	0 - 3000 m
Packet buffer memory	0.192 MB	Heat dissipation	1976.0232 BTU/h
Design		Weight & dimensions	
Rack mounting *	✓	Width	390 mm
Product colour	Grey	Depth	220 mm
Housing material	Metal	Height	43 mm
LED indicators	Activity, Link, PoE, Power, Speed	Weight	3.1 kg
Number of fans	2 fan(s)	Logistics data	
Performance		Harmonized System (HS) code	85176990
Mean time between failures (MTBF)	809853.3 h		



0606449149777



606449149777



(01)10606449149774

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.