NETGEAR GS316PP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : NETGEAR


Tuotekoodi: GS316PP-100EUS



Tuotteen nimi : GS316PP

NETGEAR GS316PP. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 4000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3at, IEEE 802.3az, IEEE 802.3az, IEEE 802.3ai, IEEE 802.3ai, IEEE 802.3az, IEEE 802.3az, IEEE 802.3ai, IEEE 802.3az, IEEE 802.3ai, IEEE 802.3az, IEEE 802.3ai, IEEE 802.3ai, IEEE 802.3az, IEE

Management features		Design	
Switch type *	Unmanaged	Wall mountable	1
Quality of Service (QoS) support	1	Performance	
Ports & interfaces		Mean time between failures (MTBF)	2362192 h
Basic switching RJ-45 Ethernet ports quantity *	16	Power	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	DC input voltage Input current	54 V 3.7 A
Power connector	DC-in jack	Power consumption (max)	195.9 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) * Power over Ethernet plus (PoE+) ports quantity	✓ 16
10G support *	×	Power over Ethernet (PoE) power per port	30 W
Full duplex Flow control support	1 1	Total Power over Ethernet (PoE) budget	183 W
Auto MDI/MDI-X	1	Operational conditions	
Auto-sensing Auto-negotiation	4 4	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 70 °C 0 - 90%
Data transmission		Operating altitude	0 - 3000 m
Switching capacity *	32 Gbit/s	Heat dissipation	669.9 BTU/h
MAC address table * Latency (1 Gbps)	4000 entries 3.7 μs	Weight & dimensions	
Jumbo frames support Jumbo frames Packet forwarding rate (1 Gbps) Packet buffer memory	 ✓ 9216 1448000 pps 1 MB 	Width Depth Height Weight	286 mm 102 mm 27 mm 880 g
Security		Certificates	
Queue scheduling algorithms	Weighted Round Robin (WRR)	Certification	CE, FCC Part A, IC A, RCM, VCCI, BSMI, KC, CB, CE LVD
Design		Logistics data	
Rack mounting * Product colour Housing material LED indicators	× Black Metal Activity, Link, PoE, Power, Speed	Harmonized System (HS) code	85176990





606449146912

0606449146912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.