## NETGEAR GS305E Hallittu Gigabit Ethernet (10/100/1000) musta

Tuotemerkki: NETGEAR Tuotekoodi: GS305E-100PES

Tuotteen nimi: GS305E



NETGEAR GS305E. Kytkin tyyppi: Hallittu. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 5. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 10 Gbit/s. Verkkostandardit: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x



Management features		Performance	
Switch type * Quality of Service (QoS) support Web-based management	Managed ✓	Noise level Buffer size Mean time between failures (MTBF)	0 dB 128 KB 2531294 h
Virtual Cable Test (VCT)	✓	Power over Ethernet (PoE)	
Ports & interfaces		Power over Ethernet (PoE) *	×
Basic switching RJ-45 Ethernet ports quantity *	3	Operational conditions Operating temperature (T-T)	0 - 50 °C
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	-20 - 70 °C 0 - 90% 0 - 95% 0 - 3000 m 0 - 3000 m
Network  Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x		
Port mirroring	<b>✓</b>	Weight & dimensions	
Flow control support Link aggregation Rate limiting	✓ × ✓	Width Depth Height Weight	94 mm 100 mm 27 mm 250 g
VLAN support Virtual LAN features	✓ Tagged VLAN, Port-based VLAN	Packaging data	
Number of VLANs	64	Package type	Вох
Data transmission		Package width	153 mm
Switching capacity * MAC address table *	10 Gbit/s 8000 entries	Package depth Package height Package weight	237 mm 61 mm 600 g
Store-and-forward Jumbo frames support	<b>√</b>	Logistics data	
Jumbo frames	9000	Master (outer) case width	344 mm
Security		Master (outer) case length Master (outer) case height	497 mm 280 mm
DHCP features	DHCP client	Harmonized System (HS) code	85176990
IGMP snooping	✓	Master (outer) case gross weight	10.2 kg
Loop protection	✓	Products per master (outer) case	15 pc(s)
Password protection	✓		
DoS attack prevention	1		

## Design

Rack mounting \* X
Product colour Black

LED indicators Activity, Link, Power, Speed, System





606449140569

0606449140569



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.