NETGEAR M4300-28G-PoE+ Hallittu L2/L3/L4 10G Ethernet (100/1000/10000) Power over Ethernet -tuki 1U musta

Tuotemerkki : NETGEAR Tuotekoodi: GSM4328PA-100NES

Tuotteen nimi: M4300-28G-PoE+

NETGEAR M4300-28G-PoE+. Kytkin tyyppi: Hallittu, Kytkinkerros: L2/L3/L4. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24, USB 2.0 -porttien määrä: 1, Console-portti: RJ-45. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 128 Gbit/s. Verkkostandardit: IEEE 802.1x, IEEE 802.3ad, IEEE 802.3az. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Security	
Switch type *	Managed	BPDU filtering/protection	✓
Switch layer	L2/L3/L4	Multicast features	
Quality of Service (QoS) support	✓	Multicast support	✓
Ports & interfaces		Number of multicast groups filtered	4000
Basic switching RJ-45 Ethernet ports quantity *	24	Design	
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Rack mounting *	✓
SFP+ module slots quantity	2	Stackable *	/
Console port	RJ-45	Form factor Product colour	1U Black
USB 2.0 ports quantity	1	Number of fans	1 fan(s)
Network		Performance	I lain(3)
Notice diagraph and *	IEEE 802.1x, IEEE 802.3ad, IEEE		
Networking standards *	802.3az	Built-in processor	✓
10G support *	✓	Processor frequency	800 MHz
Copper ethernet cabling technology	10GBASE-T	Internal memory	1024 MB
IP routing	✓	Flash memory Noise level	256 MB 39.8 dB
Auto-sensing	✓		39.8 GB
VLAN support	1	Power	
Virtual LAN features	Private VLAN	Power supply included *	✓
Number of VLANs	4096	Redundant power supply (RPS) support	✓
Data transmission		Number of power supply units	1
Switching capacity *	128 Gbit/s	AC input voltage	110 - 240 V
Forwarding rate	357 Mpps	Power consumption (typical)	577 W
MAC address table *	16000 entries	Power consumption (max)	833.2 W
Latency (10 Gbps)	2.74 μs	Power over Ethernet (PoE)	
Number of static routes	64	Power over Ethernet (PoE) *	✓
Jumbo frames support	✓	Power over Ethernet plus (PoE+)	
Packet buffer memory	16 MB	ports quantity	24
Security		Total Power over Ethernet (PoE) budget	480 W
DHCP features	DHCP server	J	
Access Control List (ACL)	✓	Operational conditions	
IGMP snooping	1	Heat dissipation	196988 BTU/h
Security algorithms	HTTPS, SNMP, SSH		

Security		Weight & dimensions	
SSH/SSL support	•	Weight	5.09 kg
		Logistics data	
		Harmonized System (HS) code	85176990





606449112771

0606449112771



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.