

## NETGEAR GS752TP Hallittu L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

**Tuotemerkki :** NETGEAR

**Tuotekoodi:** GS752TP-200EUS



**Tuotteen nimi :** GS752TP

NETGEAR GS752TP. Kytin tyyppi: Hallittu, Kytinkerros: L2/L3/L4. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48, USB 2.0 -porttien määrä: 1. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 104 Gbit/s. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U

<b>Management features</b>		<b>Multicast features</b>	
Switch type *	Managed	Multicast MAC address table	512 entries
Switch layer	L2/L3/L4	<b>Design</b>	
Web-based management	✓	Rack mounting *	✓
<b>Ports &amp; interfaces</b>		Form factor	1U
Basic switching RJ-45 Ethernet ports quantity *	48	Product colour	Black
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	LED indicators	✓
SFP module slots quantity	4	Number of fans	2 fan(s)
USB 2.0 ports quantity	1	<b>Performance</b>	
<b>Network</b>		Built-in processor	✓
10G support *	✗	Processor frequency	700 MHz
Flow control support	✓	Internal memory	128 MB
Broadcast storm control	✓	Flash memory	32 MB
Spanning tree protocol	✓	<b>Power</b>	
Ethernet LAN data rates	10,100,1000 Mbit/s	Power source *	PoE
Address Resolution Protocol (ARP) entries (max)	512	<b>Power over Ethernet (PoE)</b>	
VLAN support	✓	Power over Ethernet (PoE) *	✓
Number of VLANs	256	Power over Ethernet plus (PoE+) ports quantity	48
<b>Data transmission</b>		Total Power over Ethernet (PoE) budget	380 W
Switching capacity *	104 Gbit/s	<b>Operational conditions</b>	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 50 °C
Latency (1 Gbps)	3.35 µs	Storage temperature (T-T)	-20 - 70 °C
Static route	✓	Operating relative humidity (H-H)	0 - 90%
Jumbo frames support	✓	Storage relative humidity (H-H)	0 - 95%
Jumbo frames	10000	Operating altitude	0 - 3000 m
Packet buffer memory	1.5 MB	<b>Weight &amp; dimensions</b>	
<b>Security</b>		Width	440 mm
Access Control List (ACL) rules	100	Depth	310 mm
IGMP snooping	✓	Height	43.2 mm
<b>Multicast features</b>		Weight	5.1 kg
Multicast support	✓	<b>Logistics data</b>	
		Harmonized System (HS) code	85176990



0606449131390



606449131390

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.