NETGEAR M4250-16XF Hallittu L2/L3 1U musta

Tuotemerkki : NETGEAR Tuotekoodi: XSM4216F-100EUS

Tuotteen nimi: M4250-16XF

NETGEAR M4250-16XF. Kytkin tyyppi: Hallittu, Kytkinkerros: L2/L3. Console-portti: RJ-45/USB Type-C. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 320 Gbit/s.

Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE

802.3ad, IEEE.... Telineasennus, Kotelo: 1U

Management features		Security			
Switch type *	Managed	Authentication	MAC-based authentication		
Switch layer	L2/L3	Authentication type	RADIUS		
Quality of Service (QoS) support	✓	Multicast features			
Ports & interfaces		Multicast support	✓		
Basic switching RJ-45 Ethernet ports	×	IPv4 multicast entries	2000		
type *	•	IPv6 multicast entries	2000		
SFP+ module slots quantity Console port	16 RI-45/USB Type-C	Design			
	19-43/03В Туре-С	Rack mounting *	✓		
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Form factor	10		
		Product colour	Black		
		LED indicators	PoE, Power, Status		
		Performance			
10G support *	✓	Built-in processor	✓		
Full duplex	1	Processor model	ARM Cortex-A9		
Link aggregation	/	Processor frequency	1250 MHz		
Broadcast storm control	1	Internal memory	2048 MB		
Rate limiting	·	Noise level	56.7 dB		
_	•	Mean time between failures (MTBF)	778769 h		
Spanning tree protocol	v	Power			
VLAN support Virtual LAN features	MAC address-based VLAN, Private	Power consumption (typical)	47.84 W		
		Power over Ethernet (PoE)			
Number of VLANs	VLAN, Voice VLAN 4093	Power over Ethernet (PoE) *	×		
Data transmission	4033	Operational conditions			
	220 Chit/s	Operating temperature (T-T)	0 - 50 °C		
Switching capacity *	320 Gbit/s	Storage temperature (T-T)	-20 - 70 °C		
Throughput MAC address table *	238.08 Mpps 16000 entries	Operating relative humidity (H-H)	0 - 90%		
Store-and-forward	✓	Storage relative humidity (H-H)	0 - 95%		
		Operating altitude	0 - 3000 m		
Latency (10 Chns)	1.274 μs	Heat dissipation	163.33 BTU/h		
Latency (10 Gbps) Number of queues	0.811 μs 8	Weight & dimensions			
lumbo frames support	✓	Width	440 mm		
lumbo frames	12000	Depth	100 mm		
Packet buffer memory	16 MB	Height	43.2 mm		
	10 MB	Weight	1.74 kg		
Security		Logistics data			
DHCP features	DHCP Option 82, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 relay, DHCPv6 server, DHCPv6 snooping	Harmonized System (HS) code	85176990		
Access Control List (ACL)	✓				
IGMP snooping	✓				
SSH/SSL support	✓				
Loop protection	✓				
r r					

_						
٠,	e	c	и	ri	т١	v

BPDU filtering/protection





606449149708

0606449149708



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.