

NETGEAR MS108UP Hallitsematon 2.5G Ethernet (100/1000/2500) Power over Ethernet -tuki

Tuotemerkki : NETGEAR

Tuotekoodi: MS108UP-100EUS

Tuotteen nimi : MS108UP



NETGEAR MS108UP. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 2.5G Ethernet (100/1000/2500), Basic kytentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytentäkapasiteetti: 40 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt,.... DC-syöttöjännite: 54 V. Power over Ethernet -tuki. Seinäkiinnitteinen

Management features		Design	
Switch type *	Unmanaged	Wall mountable	✓
Quality of Service (QoS) support	✓	Number of fans	0 fan(s)
Ports & interfaces		Electromagnetic compatibility	CE, FCC part 15 Class B, ISED, VCCI, KC, CCC, BSMI, RCM
Basic switching RJ-45 Ethernet ports quantity *	8	Performance	
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Fanless	✓
2.5G Ethernet (copper) ports quantity	8	Mean time between failures (MTBF)	373643.7 h
Network		Power	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x	Power source *	DC
10G support *	✗	Power supply included *	✓
Full duplex	✓	DC input voltage	54 V
Half duplex	✓	Input current	4.7 A
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	
Head-of-line (HOL) blocking	✓	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	100,1000,2500 Mbit/s	Power over Ethernet plus (PoE+) ports quantity	8
Auto-sensing	✓	Total Power over Ethernet (PoE) budget	230 W
VLAN support	✓	Operational conditions	
Number of VLANs	64	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-20 - 70 °C
Switching capacity *	40 Gbit/s	Operating relative humidity (H-H)	0 - 90%
MAC address table *	16000 entries	Operating altitude	0 - 3000 m
Latency (1 Gbps)	3.593 µs	Heat dissipation	923.49 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Jumbo frames	12000	Width	210 mm
Packet forwarding rate (1 Gbps)	1488000 pps	Depth	140 mm
Packet buffer memory	1.5 MB	Height	40 mm
Design		Weight	900 g
Rack mounting *	✗	Certificates	
		Certification	CB, CSA, CCC, BSMI, RCM

Design

Housing material
LED indicators

Metal
Activity, Link, PoE, Power

Logistics data

Harmonized System (HS) code 85176990



0606449156874



606449156874

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.