ATEN

ATEN VE883ARK2-AT-G AV-signaalin jatkaja AV-vastaanotin musta

Tuotekoodi: VE883ARK2-AT-G

Tuotemerkki : ATEN

Tuotteen nimi : VE883ARK2-AT-G

ATEN VE883ARK2-AT-G. Malli: AV-vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Kuitu. Yhteysteknologia: Langallinen, Valokuituliitin: SFP, USB-liitin: USB A-tyyppi. Käyttöjännite: 5 V, Tehonkulutus (vastaanotin) (max): 6,5 W. Tuotteen leveys: 146,9 mm, Tuotteen syvyys: 169,4 mm, Tuotteen korkeus: 30 mm. Lukumäärä per pakkaus: 1 kpl, Pakkauksen leveys: 95 mm, Pakkauksen syvyys: 265 mm






Features		Ports & interfaces	
Type *	AV receiver	DC-in jack	1
Maximum resolution *	4096 x 2160 pixels	Power	
Cable types supported Maximum transfer distance	Fiber 10000 m	Operating voltage	5 V
Fiber optic wavelengths supported	1310 nm	Power consumption (receiver) (max)	6.5 W
Fiber mode structure	Single-mode	Operational conditions	
Electrostatic Discharge (ESD) protection	1	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Electrostatic Discharge (ESD) protection	15 kV	Operating relative humidity (H-H)	0 - 80%
LED indicators	 Image: A start of the start of	Weight & dimensions	
Supported graphics resolutions Bandwidth Bandwidth	3840 x 2160, 4096 x 2160 10.2 Gbit/s 340 MHz	Width Depth Height	146.9 mm 169.4 mm 30 mm
HDCP		Weight	660 q
Material	Metal	Packaging data	
3D	v		1 mo(n)
Rack mounting	1	Quantity per pack Package width	1 pc(s) 95 mm
Firmware upgradeable	1	Package depth	265 mm
Plug and Play	1	Package height	220 mm
Impedance	100 Ω	Package weight	265 g
HDCP version	2.2	Packaging content	
Product colour	Black	AC adapter included	1
Ports & interfaces		IR emitter included	1
Connectivity technology *	Wired	Manual	1
Ethernet LAN	✓	IR receiver included	1
RJ-45 input ports	1	Technical details	
Number of HDMI outputs Fiber optic connector	1 SFP	Country of origin	Taiwan
USB ports quantity	1	Logistics data	
USB version	2.0	Harmonized System (HS) code	85176200
USB connector type	USB Type-A	Master (outer) case width	232 mm
Remote (IR) input	1	Master (outer) case length Master (outer) case height	500 mm 283 mm

Logistics data

Master (outer) case gross weight 8.94 kg



4710469348785

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.