ATEN

ATEN VE883AK1-AT-G AV-signaalin jatkaja AV-lähetin ja vastaanotin musta

Tuotemerkki : ATEN

Tuotekoodi: VE883AK1-AT-G


Tuotteen nimi : VE883AK1-AT-G

ATEN VE883AK1-AT-G. Malli: AV-lähetin ja -vastaanotin, Enimmäiserottelutarkkuus: 4096 x 2160 pikseliä, Tuetut kaapelityypit: Kuitu. Yhteysteknologia: Langallinen, Valokuituliitin: LC, USB-liitin: Micro-USB B. Käyttöjännite: 5 V, Tehonkulutus (lähetin) (max): 7,01 W, Tehonkulutus (vastaanotin) (max): 6,5 W. Vastaanottimen mitat (L x S x K): 146,9 x 169,4 x 30 mm, Vastaanottimen paino: 660 g, Lähettimen mitat (LxSxK): 146,9 x 169,4 x 30 mm. Pakkauksen leveys: 116 mm, Pakkauksen syvyys: 540 mm, Pakkauksen korkeus: 233 mm





<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	Features		Power	
Cable types supportedFiber(max)ALL WMaximum transfer distance300 mPower consumption (receiver) (max)5. WFiber optic wavelengths supported850 nmOperating temperature (T-T)0.40 °CBidirectional*Storage temperature (T-T)0.40 °CBidirectional*Operating temperature (T-T)0.40 °CBidirectional*Operating temperature (T-T)0.40 °CBidirectional*Operating relative humidity (H-H)0.80%Protection*Weight & dimensions (WxDM)146.9 x 169.4 x 30 mmElectrostatic Discharge (ESD) protection*Receiver weight660 gSupported graphics resolutions3840 x 2160, 4096 x 2160Transmitter dimensions (WxDH)146.9 x 169.4 x 30 mmBandwidth10.2 Gbib/sTransmitter weight540 mm30Bandwidth10.2 Gbib/sTransmitter weight540 mmBandwidth10.2 Gbib/sPackage depth33 mmBandwidth10.2 Gbib/sPackage depth33 mmBandwidth16 MPackage depth30 MmJug and PlayPackage weight0.6 kgDiug and PlayPackage weight0.6 kgProtection12Ac adapter includedProtectionSincelure includedProtection12Country of origininawaBardwidth12Country of origininawaBardwidth12Country of originTesceeBardwidth </td <td>Type *</td> <td>AV transmitter & receiver</td> <td>Operating voltage</td> <td>5 V</td>	Type *	AV transmitter & receiver	Operating voltage	5 V
Caller opper supported Maximum transfer distanceNote Power consumption (receiver) (max)5.5 WFiber optic wavelengths supported Fiber optic wavelengths supported50 nmOperating returne (T-T)0.4 0 °CFiber optic wavelengths supported Bidirectional*Storage temperature (T-T)0.4 0 °CBidirectional*Operating returne through (H-H)0.8 0%Electrostatic Discharge (ESD) protection*Weight & dimensions (WxDXH)146.9 x 169.4 x 30 mmElectrostatic Discharge (SDD) protection*Receiver dimensions (WxDXH)146.9 x 169.4 x 30 mmED indicators*Receiver dimensions (WxDXH)146.9 x 169.4 x 30 mmED indicators*Transmitter dimensions (WxDXH)146.9 x 169.4 x 30 mmBandwidth10.2 Gbi/sTransmitter weight670 gBandwidth10.2 Gbi/sPackage depth470 mmDCP*Package depth30 mmJD*Package depth3.0 kgJD*Package height3.0 kgJD*Package height3.0 kgJD*Package height3.0 kgProduct colourIacPackage height3.0 kgProduct colour8.0Receiver included*Product colourKreeterReceiver included*Product colour10Receiver included*Product colourKreeterCommetric receive height%Product colourKreeterCometric receive height*Product c		•		7.01 W
Fiber optic wavelengths support880 nm Operational conditions Fiber optic kructureMulti-modeOperating temperature (T-T)0-40 °CBidirectionalStorage temperature (T-T)20 - 60 °CProtectionPerating temperature (T-T)0-80%ProtectionWeight & dimensions80%Electrostatic Discharge (ESD)TassWeight & dimensions (WxDXH)146.9 x 169.4 x 30 nmElectrostatic Discharge (ESD)Storage temperature (T-T)660 gSupported graphics resolution3840 x 2160, 4096 x 2160Transmitter dimensions (WxDXH)146.9 x 169.4 x 30 nmBandwidth340 MHzTransmitter dimensions (WxDXH)146.9 x 169.4 x 30 nm160 mmBandwidth340 MHzPackagin data116 nm116 nmBandwidth400 MHzPackagin data30 mm30 mmBandwidth400 MHzPackage weight30 do kgDCPPackage weight30 do kgJDPackage weight30 do kgPirumare upgradeableAcadapter includedPirumare upgradeable </td <td>31 II</td> <td></td> <td></td> <td>6.5 W</td>	31 II			6.5 W
Fiber mode structureMulti-modeOperating temperature (T-T)0 - 0 0 °CBidrectionalStorage temperature (T-T)20 - 60 °CBidrectionalOperating relative humidity (HH)0 - 80%Bidrectional1Multi-mode0 - 80%Bidrectional15 kVReceiver dimensions (WxDxH)146.9 x 169.4 x 30 nmBidrectionalStorage temperature (HX)600 gSupported graphics resolutions840 x 2160, 4096 x 2160Transmitter dimensions (WxDxH)146.9 x 169.4 x 30 nmBandwidth1.2 Gbit/sTransmitter dimensions (WxDxH)146.9 x 169.4 x 30 nm160Bandwidth340 MHzPactage depth50 og160Burdenal1.2 Gbit/sPackage depth30 mm160BurdenalMulti-Package depth30 seg30 segBurdenal PackageAcadge teight30 seg30 segBurdenal PackageAcadge teight30 seg30 segBurdenal PackageAcadge teight30 seg30 segBurdenal PackageScales includedScales includedScales includedBurdenal PackageScales includedScales includedScales includedBurdenal PackageScales includedScales includedScales includedBurdenal PackageScales includedScales includedScales includedBurdenal PackageScales includedScales includedScales included			Operational conditions	
Bidirectional<Storage temperature (T.T.)Electrostatic Discharge (ESD) protection </td <td>Fiber mode structure</td> <td>Multi-mode</td> <td>•</td> <td>0 - 40 °C</td>	Fiber mode structure	Multi-mode	•	0 - 40 °C
Electrostatic Discharge (ESD) protection,Operating relative humidit (H+H)0.80%Electrostatic Discharge (ESD) protection15 kVWeight & dimensions (WxDXH)146.9 x 169.4 x 30 mmElectrostatic Discharge (ESD) protection×Receiver weight660 gSupported graphics resolutions8340 x 2160.4096 x 2160Transmitter dimensions (WxDXH)146.9 x 169.4 x 30 mmBandwidth0.2 Gbit/sTransmitter weight670 gBandwidth340 MH2Package width116 mmMaterialMetalPackage width116 mmMaterialMetalPackage depth233 mmJU and Play✓Package wight306 kgPlug and Play✓Package wight306 kgPlug and Play✓AC adapter includedUSBPlote terrinoSandReceiver includedUSBPlote terrinoSandReceiver includedUSBPlote terrinoVinedReceiver includedUSBPlote terrinoSandReceiver includedSandPlote terrinoSandReceiver includedSandPlote terrinoSandCompliance certificatesReceiver includedPlote terrinoSandSandSandPlote terrinoSandCompliance certificatesReceiver includedPlote terrinoSandSandSandPlote terrinoSandSandSandPlote terrinoSandSandSandPlote terrinoSandSandS	Bidirectional	1		
Electrostatic Discharge (ESD)15 kVReceiver dimensions (WXDxH)146.9 x 169.4 x 30 mmLED indicators✓Receiver weight660 gSupported graphics resolutions3840 x 2160, 4096 x 2160Transmitter dimensions (WXDxH)146.9 x 169.4 x 30 mmBandwidth10.2 Gbit/sTransmitter weight670 gBandwidth10.2 Gbit/sTransmitter weight670 gBandwidth340 MHzPackaging dataHDCP✓Package depth540 mmMaterialMetalPackage depth233 mm3D✓Package weight233 mmJUg and Play✓Package neight3.06 kgProtect ColourBlackCalapter included✓Ports & interfacesViredReceiver included✓Ports & interfacesViredReceiver included✓RJ-45 ioutp torts1Country of originTaiwanRJ-45 output ports1Country of originTaiwanRJ-45 output ports1Logistic data375 mmNumber of HDMI outputs1Logistic data375 mmUSB ports quantity1Master (outer) case width375 mmUSB connector typeWired-USB BMaster (outer) case height258 mm	U	1		0 - 80%
protectionIndexReceiver dimensions (WxDxH)146.9 x 169.4 x 30 mmLED indicators<	U	15 kV	•	
Supported graphics resolutions3840 x 2160, 4096 x 2160Transmitter dimensions (WxDxH)146.9 x 169.4 x 30 mmBandwidth10.2 Gbit/sTransmitter weight670 gBandwidth340 MHzPackagin dataHDCPPackage width116 mmMaterialMetalPackage depth540 mm3DPackage weight233 mmJDPackage weight3.06 kgPlug and PlayPackage weight3.06 kgPlug and PlayPackage weight3.06 kgPorts & interfacesAC adapter includedPorts & interfacesR receiver includedRonctivity technology *WiredR receiver includedRJ-45 output ports1Country of originTaiwanRJ-45 output ports1Country of originTaiwanNumber of HDMI outputs1Logistics datVised connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case wight375 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm	•		, , , , , , , , , , , , , , , , , , ,	
Bandwidth10.2 Gbit/sTransmitter weight670 gBandwidth340 MHzPackagin dataHDCPImage: strain of the strain of		-	5	5
Bandwidth340 MHzPackaging dataHDCP✓Package width116 mmMaterialMetalPackage depth540 mm3D✓Package depth233 mmJTmware upgradeable✓Package weight3.06 kgPlug and Play✓Package weight3.06 kgPlug and Play✓Package weight3.06 kgPlug and Play✓Packaging contentVHDCP version2.2Caldeatr included✓Product colourBlackCaldes includedUSBPorts & interfacesIR ereciver included✓Connectivity technology*WiredIR receiver included✓RJ-45 uiput ports1Country of originTaiwanRJ-45 uiput ports1Country of originTaiwanRJ-45 uiput ports1Country of originTaiwanNumber of HDMI outputs1Logistics dataStoNumber of HDMI outputs1Master (outer) case width375 mmVSB version2.0Master (outer) case length565 mmVSB version2.0Master (outer) case height258 mm	11 5 1		· · · · ·	
HDCP··Package width116 mmMaterialMetalPackage width540 mm540 mm3D·Package depth233 mm233 mmFirmware upgradeable·Package weight3.06 kgPlug and Play·Package weight3.06 kgProduct colourBlackCadapter included·Product colourBlackCables includedUSBPorts & interfacesIR ereciver included·Connectivity technology *ViredReceiver included·RJ-45 input ports1Country of originTaiwanRJ-45 uptut ports1Country of originTaiwanHDMI in1Compliance certificatesRoHSNumber of HDMI outputs1Logistic dataS176200VISB ports quantity1Master (outer) case width375 mmUSB ports quantity2.0Master (outer) case height565 mmUSB version2.0Master (outer) case height58 mm			3	870 g
MaterialMetalPackage width116 mm3DMetalPackage depth540 mm3DIPackage height233 mmFirmware upgradeableIPackage weight3.06 kgPlug and PlayIPackaging content3.06 kgPhDCP version2.2AC adapter includedISBProduct colourBlackCables includedUSBPorts & interfacesIR ereciver includedISBConnectivity technology *WiredRreceiver includedISGRJ-45 input ports1Country of originTaiwanRJ-45 output ports1Country of originTaiwanHDMI in1Country of originRHSNumber of HDMI outputsILogistics dataS176200ISB ports quantity1.0Maser (outer) case width375 mmUSB version2.0Maser (outer) case length565 mmUSB version0.0Maser (outer) case height258 mm			Packaging data	
BDCPackage depthS40 mm3DImage depthPackage depth233 mm3DImage depthPackage height233 mmFirmware upgradeableImage depthPackage weight3.06 kgPlug and PlayImage depthPackage weight3.06 kgPlug and PlayImage depthPackage weight3.06 kgProduct colourBlackAC adapter includedImage depthPorts & interfacesImage depthImage depthImage depthPorts & interfacesImage depthImage depthImage depthConnectivity technology *Image depthImage depthImage depthRJ-45 input portsImage depthImage depthImage depthRJ-45 output portsImage depthImage depthImage depth			5	
Firmware upgradeableImage (Firmware upgradeable)Image (Firmware upgradeable)Ima				
Plug and PlayImage: content of the product of the product colourPackaging contentHDCP version2.2AC adapter includedImage: colour of the product colourProduct colourBlackCables includedUSBPorts & interfacesImage: colour of the product of the product colourImage: colour of the product of the product colourConnectivity technology *WiredImage: colour of the product o		-	5 5	
HDCP version2.2AC adapter includedProduct colourBlackCables includedUSBPorts & interfacesIR emitter includedConnectivity technology*WiredIR receiver includedEthernet LAN<		-	5 5	3.00 Kg
Product colourBlackAC adapter includedImage: Colour colourPorts & interfacesCables includedUSBPorts & interfacesIR emitter includedImage: Colour colour colourConnectivity technology *WiredIR receiver includedImage: Colour colour colourEthernet LANImage: Colour co		-	Packaging content	
Cables includedUSBPorts & interfacesIR emitter includedVConnectivity technology *WiredIR receiver included✓Ethernet LAN✓IR receiver included✓RJ-45 input ports1Country of originTaiwanRJ-45 output ports1Country of originRoHSHDMI in1Compliance certificatesRoHSNumber of HDMI outputs1Logistics dataS176200Fiber optic connectorLCHarmonized System (HS) code85176200USB version2.0Master (outer) case width375 mmUSB connector typeKiro-USB BMaster (outer) case height258 mm			AC adapter included	1
Connectivity technology *WiredIR receiver includedIR receiver includedIR receiver includedEthernet LANIIR receiver includedIR receiver includedIR receiver includedIR receiver includedRJ-45 input ports1IInternet IdeatailsInternet IdeatailsInternet IdeatailsRJ-45 output ports1Internet IdeatailsCountry of originTaiwanHDMI in1Internet IdeatailsInternet IdeatailsInternet IdeatailsNumber of HDMI outputs1Internet IdeatailsInternet IdeatailsFiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm		Didek	Cables included	USB
Ethernet LAN✓RJ-45 input ports1RJ-45 output ports1RJ-45 output ports1HDMI in1Number of HDMI outputs1Fiber optic connectorLCLCHarmonized System (HS) codeUSB ports quantity1USB connector type2.0Micro-USB BMaster (outer) case heightVerticitie258 mm			IR emitter included	1
RJ-45 input ports1Country of originTaiwanRJ-45 output ports1Country of originTaiwanHDMI in1Compliance certificatesRoHSNumber of HDMI outputs1Logistics dataFiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB connector typeKicro-USB BMaster (outer) case height258 mm	, ,,		IR receiver included	1
RJ-45 output ports1Country of originTaiwanHDMI in1Compliance certificatesRoHSNumber of HDMI outputs1Logistics dataFiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB connector type2.0Master (outer) case length565 mmUSB connector typeMaster (outer) case height258 mm			Technical details	
H745 output portsICompliance certificatesRoHSHDMI in1Logistics dataNumber of HDMI outputs1Logistics dataFiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB connector typeMicro-USB BMaster (outer) case height565 mm			Country of origin	Taiwan
Number of HDMI outputs1Logistics dataFiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB version2.0Master (outer) case length565 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm				RoHS
Fiber optic connectorLCHarmonized System (HS) code85176200USB ports quantity1Master (outer) case width375 mmUSB version2.0Master (outer) case length565 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm			Logistics data	
USB ports quantity1Master (outer) case width375 mmUSB version2.0Master (outer) case length565 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm	•		•	85176200
USB version2.0Master (outer) case length565 mmUSB connector typeMicro-USB BMaster (outer) case height258 mm	•		•	
USB connector type Micro-USB B Master (outer) case height 258 mm		2.0		
	USB connector type	Micro-USB B		
	DC-in jack	1		



4710469348730

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.