

## NETGEAR GS305Pv3 Unmanaged Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

**Brand :** NETGEAR

**Product code:** GS305P-300EUS

**Product name :** GS305Pv3



5-Port Gigabit Ethernet SOHO Unmanaged Switch with 4-Ports PoE+ (63W)

[NETGEAR GS305Pv3 Unmanaged Gigabit Ethernet \(10/100/1000\) Power over Ethernet \(PoE\) Black:](#)

5-Port Switch Gigabit Unmanaged PoE switch with 4 PoE+ ports and 63W power budget to power Wireless AP, IP Cameras, IP Phones and more.

NETGEAR GS305Pv3. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 2000 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 54 V. Power connector: DC-in jack. Power over Ethernet (PoE). Wall mountable



Management features		Design	
Switch type *	Unmanaged	Stackable *	✗
Quality of Service (QoS) support	✓	Product colour	Black
<b>Ports &amp; interfaces</b>		LED indicators	✓
Basic switching RJ-45 Ethernet ports quantity *	5	Wall mountable	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	<b>Performance</b>	
Power connector	DC-in jack	Mean time between failures (MTBF)	4113947 h
<b>Network</b>		<b>Power</b>	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power source *	DC
10G support *	✗	DC input voltage	54 V
Full duplex	✓	Input current	1.25 A
Half duplex	✓	Power consumption (max)	66.78 W
Flow control support	✓	<b>Power over Ethernet (PoE)</b>	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Power over Ethernet (PoE) power per port	30 W
Auto-sensing	✓	Total Power over Ethernet (PoE) budget	63 W
<b>Data transmission</b>		<b>Operational conditions</b>	
Switching capacity *	10 Gbit/s	Operating temperature (T-T)	0 - 40 °C
MAC address table *	2000 entries	Operating relative humidity (H-H)	0 - 90%
Jumbo frames support	✓	Operating altitude	0 - 3000 m
Jumbo frames	9216	Heat dissipation	228.38 BTU/h
Packet forwarding rate (1 Gbps)	1448000 pps	<b>Weight &amp; dimensions</b>	
Packet buffer memory	0.128 MB	Width	158 mm
<b>Design</b>		Depth	101 mm
Rack mounting *	✗	Height	27 mm
		Weight	400 g



0606449164909



606449164909

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-NOV-2024. Prints or copies of Information are only valid on the printed Publication date