

ASUS ProArt OLED PA32DC computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black

Brand : ASUS

Product family: ProArt OLED

Product code: 90LM06N0-B01I70

Product name : PA32DC



- 31.5-inch 4K (3840 x 2160) HDR OLED panel with RGB stripes and 99% DCI-P3 color gamut
 - Built-in colorimeter and ASUS Auto Calibration complement ASUS ProArt Calibration software as well as Calman and Light Illusion ColourSpace CMS professional hardware calibration software
 - True 10-bit color depth and 1,000,000:1 contrast ratio provide the deepest blacks and accurate highlights
 - Supports multiple HDR formats, including HDR10 and HLG
 - Includes two versatile stand options to suit any scenario or setup, along with an elegant metal handle for portability
 - Monitor hood helps reduce reflections, and bundled clips allow for easy cable management
- ProArt Display OLED PA32DC Professional Monitor – 31.5-inch, OLED, 4K UHD (3840 x 2160), 99% DCI-P3, Built-in Motorized Colorimeter, Auto Calibration, HDR-10, HLG, $\Delta E < 1$, USB-C, HDMI, Hardware Calibration, Calman Ready, ColourSpace Integration

Display		Ports & interfaces	
Display diagonal *	80 cm (31.5")	DisplayPorts quantity	1
Display resolution *	3840 x 2160 pixels	DisplayPort version	1.4
HD type *	4K Ultra HD	Headphone out *	✓
Native aspect ratio *	16:9	PC Audio in	✓
Display technology *	OLED	HDCP	✓
Panel type *	OLED	HDCP version	2.2
Touchscreen *	✗	Ergonomics	
Display brightness (peak)	500 cd/m ²	VESA mounting *	✓
Display brightness (typical)	250 cd/m ²	Panel mounting interface	100 x 100 mm
Response time *	0.1 ms	Cable lock slot *	✓
Display surface	Matt	Cable lock slot type	Kensington
Anti-glare screen	✓	Height adjustment *	✓
Screen shape *	Flat	Adjustable height (max)	13 cm
Contrast ratio (typical) *	1000000:1	Pivot	✓
Maximum refresh rate *	60 Hz	Pivot angle	-90 - 90°
Viewing angle, horizontal	178°	Swivelling	✓
Viewing angle, vertical	178°	Swivel angle range	-30 - 30°
Display number of colours *	1.073 billion colours	Tilt adjustment	✓
Pixel pitch	0.182 x 0.182 mm	Tilt angle range	-5 - 23°
Viewable size, horizontal	69.8 cm	Power	
Viewable size, vertical	39.3 cm	Energy efficiency class (SDR) *	G
Digital horizontal frequency	31 - 135 kHz	Energy efficiency class (HDR) *	G
Digital vertical frequency	24 - 75 Hz	Energy consumption (SDR) per 1000 hours *	46 kWh
High Dynamic Range (HDR) supported	✓	Energy consumption (HDR) per 1000 hours *	75 kWh
High Dynamic Range (HDR) technology	Dolby Vision, High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)	Power consumption (typical) *	38 W
Colour depth	10 bit		
Colour gamut standard	DCI-P3		

Display		Power	
Colour gamut	99%	Power consumption (off)	0 W
Adobe RGB coverage	99%	Power consumption (PowerSave)	0.5 W
Performance		AC input voltage	100 - 240 V
NVIDIA G-SYNC *	✗	AC input frequency	50 - 60 Hz
AMD FreeSync *	✗	Energy efficiency scale	A to G
Flicker-free technology	✓	European Product Registry for Energy Labelling (EPREL) code	1115602
Low Blue Light technology	✓	Weight & dimensions	
Multimedia		Width (with stand)	735.4 mm
Number of speakers	2	Depth (with stand)	245 mm
RMS rated power	6 W	Height (with stand)	626.9 mm
Built-in speaker(s) *	✓	Weight (with stand)	12.1 kg
Built-in camera *	✗	Width (without stand)	735.4 mm
Design		Depth (without stand)	54.4 mm
Market positioning *	Graphics design	Height (without stand)	466.9 mm
Product colour *	Black	Weight (without stand)	7.6 kg
Detachable stand	✓	Packaging data	
Feet colour	Black	Package width	878 mm
Ports & interfaces		Package depth	298 mm
Built-in USB hub *	✓	Package height	616 mm
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Package weight	19.9 kg
USB upstream port type	USB Type-C	Package type	Box
Number of upstream ports	1	Packaging content	
Number of USB Type-C upstream ports quantity	1	Stand included	✓
USB Type-A downstream ports quantity	4	Cables included	AC, DisplayPort, HDMI, USB Type-C, USB Type-C to USB Type-A
USB Power Delivery (USB PD)	✓	Sun hood included	✓
USB Power Delivery up to	65 W	Quick start guide	✓
HDMI *	✓	Other features	
HDMI ports quantity	3	Certification	Energy Star TÜV Flicker-free TÜV Low Blue Light VESA DisplayHDR 400 True Black Calman Ready
HDMI version	2.0		



4711081560883



0195553560931



195553560931

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.