



AOC V5 CU34V5C/BK/23 LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black

Brand : AOC

Product family: V5

Product code: CU34V5C/BK/23

Product name :
CU34V5C/BK/23

Screen size (inch) 34, Panel resolution 3440x1440, Max Refresh rate 100 Hz, Response time MPRT 1 ms, Panel type VA, USB-C connectivity USB-C 3.2 x 1 (DP alt mode, upstream, power delivery up to 65 W), HDMI HDMI 2.0 x 1, Display Port DisplayPort 1.2 x 1, D-SUB (VGA) 0x, DVI 0x, Sync technology (VRR) Freesync

AOC V5 CU34V5C/BK/23 LED display 86.4 cm (34") 3440 x 1440 pixels Wide Quad HD Black:

34" VA WQHD panel for maximum productivity, with MultiView, USB-C and PD65W

The AOC CU34V5C is equipped with a 34" VA curved panel with Ultrawide QHD 21:9 resolution for an immersive viewing experience in a three-side frameless chassis that you can tilt and height adjust as needed. Ready to boost your productivity with USB-C with Power Delivery up to 65W, 4 USB ports & HDMI, it also offers Picture by Picture MultiView for the most complex multitasking.



Display		Ports & interfaces	
Display diagonal *	86.4 cm (34")	Headphone out *	✓
Display resolution *	3440 x 1440 pixels	Headphone outputs	1
HD type *	Wide Quad HD	Headphone connectivity	3.5 mm
Native aspect ratio *	21:9	HDCP	✓
Display technology *	LED	HDCP version	2.2
Panel type *	VA	AC (power) in	✓
Backlight type	W-LED	Mobile High-Definition Link (MHL)	✗
Touchscreen *	✗	Ergonomics	
Display brightness (typical)	300 cd/m ²	VESA mounting *	✓
Response time *	1 ms	Panel mounting interface	100 x 100 mm
Anti-glare screen	✓	Wall mountable	✓
Screen shape *	Curved	Cable lock slot *	✓
Screen curvature rating	1500R	Cable lock slot type	Kensington
Contrast ratio (typical) *	3000:1	Height adjustment *	✓
Contrast ratio (dynamic)	20000000:1	Height adjustment	13 cm
Maximum refresh rate *	100 Hz	Pivot	✗
Viewing angle, horizontal	178°	Swivelling	✓
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.7 million colours	Tilt angle range	3 - 21°
Pixel pitch	0.23175 x 0.23175 mm	Picture-in-Picture	✓
Pixel density	109.7 ppi	On Screen Display (OSD)	✓
Display diagonal (metric)	86.4 cm	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Surface hardness	6H	Number of OSD languages	19
sRGB coverage (typical)	116%		
NTSC coverage (typical)	101%		
Adobe RGB coverage	100%		
DCI-P3 coverage	93%		

Performance		Ergonomics	
NVIDIA G-SYNC *	✗	LED indicators	✓
AMD FreeSync *	✓	Power	
AMD FreeSync type	FreeSync	Energy efficiency class (SDR) *	G
Fast charging	✓	Energy efficiency class (HDR) *	G
Flicker-free technology	✓	Energy consumption (SDR) per 1000 hours *	34 kWh
Low Blue Light technology	✓	Energy consumption (HDR) per 1000 hours *	35 kWh
Brand-specific features	False	Power consumption (typical) *	60 W
Multimedia		Power consumption (standby) *	0.5 W
Number of speakers	2	Power consumption (off)	0.3 W
RMS rated power	10 W	Power supply type	Internal
Built-in speaker(s) *	✓	Energy efficiency scale	A to G
Built-in microphone	✗	European Product Registry for Energy Labelling (EPREL) code	1245431
Built-in camera *	✗	Weight & dimensions	
Design		Width (with stand)	808.1 mm
Market positioning *	Home	Depth (with stand)	250 mm
Product colour *	Black	Height (with stand)	527.3 mm
Frameless design	✓	Weight (with stand)	9.34 kg
Front bezel colour	Black	Width (without stand)	808.1 mm
Detachable stand	✓	Depth (without stand)	99.9 mm
Feet colour	Black	Height (without stand)	365.3 mm
Ports & interfaces		Packaging data	
Built-in USB hub *	✓	Package width	189 mm
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package depth	1071 mm
USB upstream port type	USB Type-C	Package height	500 mm
Number of upstream ports	1	Package weight	11.8 kg
Number of USB Type-C upstream ports quantity	1	Package type	Box
USB Type-A downstream ports quantity	4	USB cable length	1.8 m
USB Type-C DisplayPort Alternate Mode	✓	Packaging content	
USB Power Delivery (USB PD)	✓	Stand included	✓
USB Power Delivery up to	65 W	Cables included	AC
DVI port	✗	HDMI cable length	1.5 m
HDMI *	✓	Other features	
HDMI ports quantity	1	Picture-by-Picture (PbP)	✓
HDMI version	2.0	Exterior finish type	Matt
DisplayPorts quantity	1	Mean time between failures (MTBF)	50000 h
DisplayPort version	1.2	Light effects	✗

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date