NOC

AOC B3 Q27B3CF2/23 tietokoneen litteä näyttö 68,6 cm (27") 2560 x 1440 pikseliä Quad HD musta

Tuotemerkki : AOC Tuoteperhe: B3 Tuotekoodi: Q27B3CF2/23

Tuotteen nimi: Q27B3CF2/23

AOC B3 Q27B3CF2/23. Näytön halkaisija: 68,6 cm (27"), Näytön erottelutarkkuus: 2560 x 1440 pikseliä, HD-tyyppi: Quad HD, Vasteaika (tyypillinen): 1 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäiset kaiuttimet. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäätö. Tuotteen väri: musta





| Display | | Ports & interfaces | |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------|
| Display diagonal * Display resolution * | 68.6 cm (27") 2560 x 1440 pixels | USB Type-C downstream ports quantity | 1 |
| HD type * Native aspect ratio * | Quad HD 16:9 | USB Type-C DisplayPort Alternate Mode | ✓ |
| Panel type * | IPS | USB Power Delivery (USB PD) | ✓ 65 W |
| LED backlight Backlight type | ✓ W-LED | USB Power Delivery up to HDMI * HDMI ports quantity HDMI version Headphone out * Headphone outputs Headphone connectivity HDCP HDCP version AC (power) in | 1 2.0 1 3.5 mm |
| Touchscreen * | × | | |
| Display brightness (typical) Response time * | 350 cd/m² 1 ms | | |
| Anti-glare screen Screen shape * | ✓ Flat | | |
| Contrast ratio (typical) * | 1500:1 | | |
| Contrast ratio (dynamic) Maximum refresh rate * | 20000000:1 100 Hz | | |
| Viewing angle, horizontal | 178° | Ergonomics | |
| Viewing angle, vertical Display number of colours * Pixel pitch Pixel density Horizontal scan range Vertical scan range Display diagonal (metric) DDC/CI Haze rate Surface hardness | 178° 16.7 million colours 0.2331 x 0.2331 mm 109 ppi 30 - 115 kHz 48 - 100 Hz 68.6 cm ✓ 25% 3H | VESA mounting * Panel mounting interface Cable lock slot type Height adjustment * Height adjustment Tilt adjustment Tilt angle range Plug and Play LED indicators | ✓ 100 x 100 mm Kensington ✓ 11 cm ✓ -5 - 25° ✓ Operation, Stand-by |
| Colour gamut standard | sRGB | Power | |
| Colour gamut sRGB coverage (typical) NTSC coverage (typical) Adobe RGB coverage | 99% 120.8% 105.3% 103.5% | Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) | 35 W 0.5 W 135 W 0.3 W |

| Display | | Power | |
|--------------------------------------|-----------------------|------------------------|------------------------------------|
| BT.2020 coverage | 70.1% | AC input voltage | 100 - 240 V |
| Performance | | AC input frequency | 50/60 Hz |
| VESA Adaptive Sync support | √ | Power supply type | Internal |
| Flicker-free technology | 1 | Weight & dimensions | |
| Low Blue Light technology | · | Width (with stand) | 616.6 mm |
| | • | Depth (with stand) | 229.8 mm |
| Multimedia | | Height (with stand) | 508.6 mm |
| Number of speakers | 2 | Weight (with stand) | 5.51 kg |
| RMS rated power | 4 W | Width (without stand) | 616.6 mm |
| Built-in speaker(s) * | ✓ | Depth (without stand) | 45.6 mm |
| Built-in camera * | × | Height (without stand) | 356.7 mm |
| Design | | Weight (without stand) | 3.97 kg |
| Market positioning * | Home | Packaging data | |
| Product colour * | Black | Package width | 820 mm |
| Front bezel colour | Black | Package depth | 162 mm |
| Detachable stand | ✓ | Package height | 481 mm |
| Ports & interfaces | | Package weight | 8.62 kg |
| | | Package type | Box |
| Built-in USB hub * | • | Packaging content | |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) | Stand included | 1 |
| USB Type-A downstream ports quantity | 2 | Cables included | AC, HDMI, USB Type-C to USB Type-C |
| | | HDMI cable length | 1.5 m |
| | | Other features | |
| | | | |

