

PHILIPS

Philips Evnia 5000 32M2C5500W/00 tietokoneen litteä näyttö 80 cm (31.5") 2560 x 1440 pikseliä Quad HD LCD musta

Tuotemerkki : Philips

Tuoteperhe: Evnia

Tuotekoodi: 32M2C5500W/00

Tuotteen nimi :
32M2C5500W/00

Gaming Monitor 32M2C5500W Quad HD -pelinäyttö

Philips Evnia 5000 32M2C5500W/00 tietokoneen litteä näyttö 80 cm (31.5") 2560 x 1440 pikseliä Quad HD LCD musta:

Koe näytön 240 Hz:n virkistystaajuus ja MPRT-arvo 0,5. Näytössä on lisäksi korkea kontrasti, laadukas HDR 400 -kuva sekä selkeä Quad HD -laatu, mikä varmistaa täydellisen pelikokemuksen. Philips Evnia 5000 32M2C5500W/00. Näytön halkaisija: 80 cm (31.5"), Näytön erottelutarkkuus: 2560 x 1440 pikseliä, HD-tyyppi: Quad HD, Näytön teknologia: LCD, Vasteaika (tyypillinen): 1 ms, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. Sisäänrakennettu USB-keskus, USB-keskuksen versio: 3.2 Gen 1 (3.1 Gen 1). VESA-kiinnitys, Korkeudensäättö. Tuotteen väri: musta



Display		Ergonomics	
Display diagonal *	80 cm (31.5")	Panel mounting interface	100 x 100 mm
Display resolution *	2560 x 1440 pixels	Cable lock slot *	✓
HD type *	Quad HD	Cable lock slot type	Kensington
Native aspect ratio *	16:9	Height adjustment *	✓
Display technology *	LCD	Height adjustment	13 cm
Panel type *	VA	Swivelling	✓
Backlight type	W-LED	Swivel angle range	-30 - 30°
Touchscreen *	✗	Tilt adjustment	✓
Display brightness (typical)	500 cd/m ²	Tilt angle range	-5 - 20°
Response time *	1 ms	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Anti-glare screen	✓	Plug and Play	✓
Screen shape *	Curved	LED indicators	Operation, Stand-by
Contrast ratio (typical) *	4000:1		
Maximum refresh rate *	240 Hz	Power	
Viewing angle, horizontal	178°	Energy efficiency class (SDR) *	F
Viewing angle, vertical	178°	Power consumption (typical) *	39.36 W
Display number of colours *	16.7 million colours	Power consumption (standby) *	0.5 W
Response time (fast)	0.5 ms	Power consumption (off)	0.3 W
Pixel pitch	0.2724 x 0.2724 mm	AC input voltage	100 - 240 V
Pixel density	93.24 ppi	AC input frequency	50/60 Hz
Horizontal scan range	30 - 255 kHz	Power supply type	Internal
Vertical scan range	48 - 144 Hz		
Viewable size, horizontal	69.7 cm	Operational conditions	
Viewable size, vertical	39.2 cm	Operating temperature (T-T)	0 - 40 °C
Display diagonal (metric)	80 cm	Storage temperature (T-T)	-20 - 60 °C
High Dynamic Range (HDR) technology	DisplayHDR 400	Operating relative humidity (H-H)	20 - 80%
DDC/CI	✓	Operating altitude	0 - 3658 m
Haze rate	25%	Non-operating altitude	0 - 12192 m
Surface hardness	3H		
Colour depth	8 bit		
sRGB coverage (typical)	122%		

Display		Weight & dimensions	
NTSC coverage (typical)	100%	Width (with stand)	700 mm
DCI-P3 coverage	92%	Depth (with stand)	320 mm
Display sRGB	✓	Height (with stand)	601 mm
Performance		Weight (with stand)	8.35 kg
AMD FreeSync *	✓	Width (without stand)	700 mm
AMD FreeSync type	FreeSync Premium Pro	Depth (without stand)	131 mm
VESA Adaptive Sync support	✓	Height (without stand)	426 mm
Component video sync	Separate sync	Weight (without stand)	6.5 kg
Flicker-free technology	✓	Packaging data	
Design		Package width	900 mm
Product colour *	Black	Package depth	226 mm
Ports & interfaces		Package height	527 mm
Built-in USB hub *	✓	Package weight	11.1 kg
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Packaging content	
Number of USB Type-B upstream ports quantity	1	Stand included	✓
USB Type-A downstream ports quantity	4	Manual	✓
HDMI *	✓	Sustainability	
HDMI ports quantity	2	Doesn't contain	Mercury, PVC/BFR
HDMI version	2.0	Other features	
DisplayPorts quantity	2	Low input lag	✓
DisplayPort version	1.4	Exterior finish type	Textured
Audio output	✓	Picture enhancement	SmartImage game
HDCP	✓	Recyclable packaging material	100%
HDCP version	1.4/2.2	Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CCC; CECP; CEL
Ergonomics		Delta E	2
VESA mounting *	✓	EasyRead mode	✓
		LowBlue mode	✓
		Philips SmartUniformity	93 - 105%
		Mean time between failures (MTBF)	50000 h



8712581799564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-DEC-2024. Prints or copies of Information are only valid on the printed Publication date