

ZYXEL

## Zyxel XGS1210-12-ZZ0102F verkkokytkin Hallittu Gigabit Ethernet (10/100/1000) Harmaa

**Tuotemerkki** : Zyxel

**Tuotekoodi**: XGS1210-12-ZZ0102F

**Tuotteen nimi** : XGS1210-12-ZZ0102F



Zyxel XGS1210-12-ZZ0102F. Kytkin tyyppi: Hallittu. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 66 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az. DC-syöttöjännite: 12 V



<b>Management features</b>		<b>Multicast features</b>	
Switch type *	Managed	Multicast support	✓
Quality of Service (QoS) support	✓	<b>Design</b>	
Web-based management	✓	Product colour	Grey
<b>Ports &amp; interfaces</b>		Reset button	✓
Basic switching RJ-45 Ethernet ports quantity *	8	LED indicators	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Number of fans	0 fan(s)
2.5G Ethernet (copper) ports quantity	2	<b>Power</b>	
SFP+ module slots quantity	2	Power source *	AC/DC
<b>Network</b>		Power supply included *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3az	AC input voltage	100 - 240 V
Full duplex	✓	DC input voltage	12 V
Flow control support	✓	Input current	1.5 A
Link aggregation	✓	Power consumption (max)	15.61 W
Broadcast storm control	✓	<b>Operational conditions</b>	
Auto MDI/MDI-X	✓	Operating temperature (T-T)	0 - 40 °C
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	10 - 90%
<b>Data transmission</b>		Storage relative humidity (H-H)	10 - 90%
Switching capacity *	66 Gbit/s	<b>Weight &amp; dimensions</b>	
Forwarding rate	49 Mpps	Width	250 mm
MAC address table *	16000 entries	Depth	104 mm
Static route	✓	Height	24 mm
		Weight	768 g
		<b>Packaging data</b>	
		Package width	306 mm
		Package depth	225 mm

Data transmission		Packaging data	
Jumbo frames support	✓	Package height	64 mm
Jumbo frames	12000	Package weight	1.22 kg
Packet buffer memory	1.5 MB	Logistics data	
Security		Harmonized System (HS) code	85176990
DHCP features	DHCP client		
IGMP snooping	✓		
Loop protection	✓		



4718937633715

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 22-DEC-2024. Prints or copies of Information are only valid on the printed Publication date