

Kodak S2070 ADF-skanneri 600 x 600 DPI A4 musta, Valkoinen

Tuotemerkki : Kodak Alaris

Tuoteperhe: Kodak

Tuotekoodi: 1015049

Tuotteen nimi : S2070



Kodak S2070. Skannauksen enimmäiskoko: 216 x 3000 mm, Optinen skannauserottelutarkkuus: 600 x 600 DPI, Tulon värisyvyys: 30 bittiä. Skannerityyppi: ADF-skanneri, Tuotteen väri: musta, Valkoinen, Näyttö: LCD. Anturin tyyppi: Dual CIS, Päivittäinen käyttöjakso (maks.): 7000 sivua, Valonlähde: RGB LED. Vakiosyöttökapasiteetti (arkkia): 80 arkkaa, Automaattisen asiakirjojen syöttölaitteen kapasiteetti: 80 arkkaa. Suurin ISO A-luokan paperikoko: A4, Tuetut skannausmediatyypit: Tavallinen paperi, Muovikortti, Uusiopaperi, Paksu paperi, Ohut paperi, ISO A-sarjan koot (A0...A9): A4

Scanning		Ports & interfaces	
Maximum scan size *	216 x 3000 mm	Standard interfaces	USB 3.2 Gen 1 (3.1 Gen 1)
Optical scanning resolution *	600 x 600 DPI	Power	
Colour scanning	✓	Power supply type *	AC
Duplex scanning *	✓	Power consumption (typical)	36 W
Input colour depth	30 bit	Power consumption (standby)	3 W
Output colour depth	24 bit	Power consumption (off)	0.5 W
Output greyscale depth	8 bit	Power consumption (PowerSave)	3 W
Film scanning	✗	AC input frequency	50 - 60 Hz
Greyscale levels	256	Input voltage	100-240 V
ADF scan speed (b/w, A4)	70 ppm	Power supply	36 W
ADF scan speed (greyscale, A4)	70 ppm	Weight & dimensions	
ADF scan speed (colour, A4)	70 ppm	Width	312 mm
Duplex ADF scan speed (b/w, A4)	140 ipm	Depth	204 mm
Duplex ADF scan speed (colour, A4)	140 ipm	Height	182.5 mm
Black/white scanning colour modes	Grayscale	Weight	3.3 kg
Design		Packaging content	
Scanner type *	ADF scanner	Cables included	AC, USB
Product colour *	Black, White	ADF paper chute	✓
Display	LCD	Stacker	✓
Display diagonal	3.81 cm (1.5")	Drivers included	✓
Touchscreen	✗	Bundled software WINDOWS Bundled software: TWAIN, ISIS, WIA Drivers; Alaris Capture Pro Limited, Smart Touch, LINUX drivers available from www.kodak.com/go/scanonlinux (September Availability) KOFAX certified. (Future Availability)	
Built-in display *	✓		
Performance		Sustainability	
Sensor type *	Dual CIS	Sustainability certificates	ENERGY STAR
Light source	RGB LED	System requirements	
Scan file formats	BMP, CSV, DOC, JPG, PDF, PNG, RTF, TIFF, TXT, XLS	Minimum RAM	4000 MB
Daily duty cycle (max) *	7000 pages	Minimum processor	INTEL CORE i3 - 4150 processor
Scan to	Cloud, E-mail, E-mail Server, File, Image, OCR, PC, TWAIN, WIA	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Button functions	Cancel, Down, Off, On, Scan, Up		
Scan drivers	ISIS, TWAIN, WIA		
Barcode reader	✓		
Built-in processor	✓		

Performance		Operational conditions	
Processor frequency	1500 MHz	Operating temperature (T-T)	10 - 35 °C
Input capacity		Operating relative humidity (H-H)	15 - 80%
Standard input capacity	80 sheets	Operating temperature (T-T)	50 - 95 °F
Auto document feeder (ADF) input capacity	80 sheets	Other features	
Paper handling		Downloadable software	Capture Pro Limited Edition, Smart Touch
Scanning media types supported	Plain paper, Plastic Card, Recycled paper, Thick paper, Thin paper	Selectable background colour	✗
Multi feed detection	✓	Certification	EPEAT Registered ENERGY STAR Qualified AS/NZS CISPR 22:2009 +A1:2010; (Class B RCM mark), CAN / CSA - C22.2 No 60950-1-07 +A1:2011 (TUV C mark), Canada CSA-CISPR 22-10 / ICES-003 Issue 5 (Class B), China GB4943.1:2011; GB9254:2008 Class B (CCC S&E mark), EN55022:2010 ITE Emissions (Class B), EN55024:2010 ITE Immunity (CE mark), EN60950-1:2006 +A1,+A11,+A12 (TUV GS mark), IEC60950-1:2005 +A1, Taiwan CNS 13438:2006 (Class B); CNS 14336-1 (BSMI mark), UL 60950-1:2007 R12.11 (TUV US mark), CFR 47 Part 15 (FCC Class B), Argentina S mark
Maximum ISO A-series paper size *	A4		
ISO A-series sizes (A0...A9)	A4		
Legal	✓		
Auto Document Feeder (ADF) media weight	27 - 433 g/m ²		
Maximum scan width	21.6 cm		
Maximum scan length	3 m		
Maximum scan area (ADF)	216 x 356 mm		
Minimum scan area (ADF)	52 x 52 mm		
Ports & interfaces			
USB port *	✓		
USB version	3.2 Gen 2 (3.1 Gen 2)		
Technical details		Linear (1D) barcodes supported	Codabar, Code 128, Code 3 of 9, EAN-13, EAN-8, PDF417, U.P.C.
PC connection		Scan technology	Dual CIS
Scan technology		Maximum paper size	216 x 3000 mm
Maximum paper size		Relative humidity	15 - 80%
Relative humidity		Power	36 W
Power		Logistics data	
		Harmonized System (HS) code	84716070



0041771015046



041771015046

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.