


Acer X1526HK data projector Standard throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White

Brand : Acer Product code: MR.JV611.001

Product name: X1526HK



of light source (economic mode): 10000 h. Focal length range: 15.85 - 17.44 mm, Aperture range (F-F): 2 - 2.05, Throw ratio: 1.5 - 1.65. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 1920×1080 (HD 1080), 1920×1200 (WUXGA). Serial interface type: RS-232





Projector		Ports & interfaces	
Supported aspect ratios	ion distance 1 - 10 m	Mobile High-Definition Link (MHL)	×
Projection distance		Network	
Projector brightness * 4000 ANSI lumens Projection technology * DLP Projector native resolution * 1080p (1920x1080) Contrast ratio (typical) * 10000:1		Smart TV *	×
		Ethernet LAN *	×
	10000:1	Storage	
Native aspect ratio *	16:9	Card reader integrated *	×
Number of colours	1.07 billion colours 15 - 100 kHz	Features	
Horizontal scan range Vertical scan range	15 - 100 kHz 24 - 120 Hz	Interactive *	
Keystone correction, vertical	-40 - 40°	Noise level (economic mode)	X 26 dB
Light source		Projection modes	Ceiling, Front, Rear
Light source type *	Lamp	Noise level *	32 dB
Service life of light source *	4000 h	Multimedia	
Service life of light source (economic mode)	10000 h	Built-in speaker(s) *	✓
Lamp type	OSRAM	RMS rated power	3 W
Lamp power	245 W	Number of built-in speakers	1
Lamps quantity	1 lamp(s)	Design	
Lens system		Market positioning *	Business
Focal length range	15.85 - 17.44 mm	Product type *	Standard throw projector
Aperture range (F-F)	2 - 2.05	Product colour * Placement	White Ceiling
Zoom capability	•		Centrig
Throw ratio	1.5 - 1.65	Display	
Video		Built-in display *	×
Analog signal format system *	NTSC, PAL, SECAM	Power	
Full HD *	✓	Power source *	AC 290 W
3D *	X 1920 x 1080 (HD 1080), 1920 x	Power consumption (typical) * AC input voltage	120 - 230 V
Supported graphics resolutions	1920 X 1080 (HD 1080), 1920 X 1200 (WUXGA)	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
USB 2.0 ports quantity	1	Weight & dimensions	
Audio (L/R) in *	1	Width	322 mm
Audio (L/R) out	1	Depth	225 mm
Serial interface type *	RS-232 2	Height	91 mm
HDMI ports quantity *	۷	Weight *	2.6 kg

Ports & interfaces		Packaging content	
DVI port *	×	Remote control included *	✓
		Batteries included	✓
		Cables included	AC
		Manual	✓
		Logistics data	
		Quantity per pack	1 pc(s)



4711121000379

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.