Canon

Canon i-SENSYS MF754CDW Laser A4 1200 x 1200 DPI 33 ppm Wi-Fi

Brand : Canon Product family: i-SENSYS Product code: 5455C009

Product name: MF754CDW

Print, copy, Scan, Fax, 33ppm, A4, 1024MB, LAN, USB, WiFi, LCD Canon i-SENSYS MF754CDW. Print technology: Laser, Printing: Colour printing, Maximum resolution: 1200 x 1200 DPI. Copying: Colour copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Colour faxing. Duplex functions: Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Product colour: White





| Printing | | Paper handling | |
|--|--|---|--|
| Print technology * Printing * Maximum resolution * Print speed (black, normal quality, | Laser Colour printing 1200 x 1200 DPI 33 ppm | ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes Paper tray media weight | B5 Executive, Letter, Statement C5, Com-10, DL, Monarch 60 - 200 g/m ² |
| A4/US Letter) * Warm-up time | 14 s | Ports & interfaces | |
| Time to first page (black, normal) Time to first page (colour, normal) | 7.1 s 7.1 s | USB port USB 2.0 ports quantity | 1 |
| Copying | | Network | |
| Duplex copying * Copying * Maximum copy resolution * Maximum number of copies | Colour copying 600 x 600 DPI 999 copies 25 - 400% | Wi-Fi * Ethernet LAN * Ethernet LAN data rates Wi-Fi standards | 10,100,1000 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n) |
| Copier resize ID-card copy function | ∠3 - 400% ✓ | Security algorithms | 64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP |
| Scanning | | Management protocols | SNMPv1, SNMPv3 (IPv4,IPv6) |
| Duplex scanning * Scanning * Optical scanning resolution * Scanner type * Scan to Input colour depth Output colour depth | Colour scanning 600 x 600 DPI ADF scanner Cloud, E-mail, FTP, USB 24 bit 24 bit | Performance Internal memory * Built-in processor Processor frequency Sound power level (printing) Sound power level (standby) | 1024 MB ✓ 1200 MHz 65 dB 41 dB |
| Greyscale levels | 256 | Design | |
| Scan drivers | ICA, TWAIN, WIA | Product colour * | White |
| Fax Faxing * Modem speed Fax memory | Colour faxing 33.6 Kbit/s 512 pages | Market positioning * Built-in display * Display Control type | Business LCD Touch |

| Features | | Power | | |
|---|---|--|--|--|
| Recommended duty cycle Maximum duty cycle * Duplex functions * Printing colours * | 750 - 4000 pages per month 50000 pages per month Scan Black, Cyan, Magenta, Yellow | Power consumption (max) Power consumption (printing) Power consumption (standby) Power consumption (sleep) | 1380 W 700 W 24 W 1 W | |
| Input & output capacity | | Energy Star Typical Electricity | 0.3 kWh/week | |
| Total number of input trays * Total input capacity * | 1 250 sheets 150 sheets | Consumption (TEC) AC input voltage AC input frequency | 220 - 240 V 50 - 60 Hz | |
| Total output capacity * | | System requirements | | |
| Multi-Purpose tray input capacity 50 sheets | 50 sheets | Windows operating systems supported | Windows 10, Windows 11, Windows 8.1 | |
| Auto document feeder (ADF) Auto document feeder (ADF) input capacity | 50 sheets | 10 Mo | Mac OS X 10.12 Sierra, Mac OS X L0.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, | |
| Maximum input capacity | 850 sheets | | Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 | |
| Paper handling | | Mac operating systems supported | systems supported Panther, Mac OS X 10.4 Tiger, Mac | |
| Maximum ISO A-series paper size * Paper tray media types * | A4 Coated paper, Envelopes, Heavy paper, Plain paper, Postcard, Recycled paper, Thin paper | Snow Leo Mac OS X OS X 10.9 | OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey | |
| ISO A-series sizes (A0A9) * | A4, A5, A6 | Linux operating systems supported | ✓ | |
| | | Server operating systems supported | Windows Server 2022, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019 | |
| | | Operational conditions | | |
| | | Operating relative humidity (H-H) Operating temperature (T-T) | 20 - 80% 10 - 30 °C | |
| | | Weight & dimensions | | |
| | | Width | 425 mm | |
| | | Depth | 461 mm | |
| | | Height | 430 mm | |
| | | Weight | 23.3 kg | |



4549292193152

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.