

DELL P Series 27 USB-C Hub Monitor - P2723DE

Brand : DELL Product family: P Series Product code: DELL-P2723DE

Product name : Dell 27 USB-C Hub Monitor - P2723DE

- 68.6cm (27") Quad HD 2560 x 1440 LED IPS
- 5ms, 16:9, 350cd/m², 1000:1
- USB, HDMI, DisplayPort

68.6cm (27") Quad HD 2560 x 1440 LED IPS, 16:9, 350cd/m², 16.7M, 5ms, 178°/178°, 1000:1

DELL P Series 27 USB-C Hub Monitor - P2723DE:

Experience pure productivity on a 27-inch QHD monitor featuring extensive connectivity and ComfortView Plus.

DELL P Series 27 USB-C Hub Monitor - P2723DE. Display diagonal: $68.6 \text{ cm } (27^{\circ})$, Display resolution: $2560 \times 1440 \text{ pixels}$, HD type: Quad HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178° , Viewing angle, vertical: 178° . Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology *	ution * 2560 x 1440 pixels Quad HD t ratio * 16:9 LCD	Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play	-45 - 45° ✓ -5 - 21° ✓
Panel type *	IPS	Power	
Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Supported video modes	LED X 350 cd/m² 5 ms ✓ Flat 480p, 576p, 720p, 1080i, 1080p, 1440p	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off)	F Not available 26 kWh 26 W 0.3 W 175 W 0.3 W
Contrast ratio (typical) *	1000:1	AC input voltage	100 - 240 V
Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch	60 Hz 178° 178° 16.7 million colours 8 ms 0.2331 x 0.2331 mm	AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	50 - 60 Hz 2 A Internal A to G
Pixel density	109 ppi	Operational conditions	
Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Viewable size diagonal Display diagonal (metric)	29 - 113 kHz 49 - 75 Hz 59.7 cm 33.6 cm 68.5 cm 68.47 cm	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 20 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m

Display		Weight & dimensions	
High Dynamic Range (HDR)		Width (with stand)	611.6 mm
supported	×	Depth (with stand)	190.1 mm
Colour gamut standard	sRGB	Height (with stand)	535.2 mm
Colour gamut	99%	Weight (with stand)	6.55 kg
Performance		Width (without stand)	611.6 mm
NVIDIA G-SYNC *	×	Depth (without stand)	52.2 mm
AMD FreeSync *	x	Height (without stand)	360.8 mm
Low Blue Light technology	7	Weight (without stand)	5.07 kg
	•	Bezel width (side)	7.43 mm
Multimedia		Bezel width (top)	7.37 mm
Built-in speaker(s) *	X	Bezel width (bottom)	1.78 cm
Built-in camera *	×	Packaging data	
Design		Package weight	9.78 kg
Market positioning * Product colour *	Business Black	Packaging content	
Front bezel colour	Black	Stand included	✓
Detachable stand	✓ Silver	Cables included	AC, DisplayPort, USB Type-C to USB Type-A
Feet colour	Silvei	Quick start guide	✓
Ports & interfaces		Carbon footprint	
Built-in USB hub *	V USD To a C	Total carbon footprint (kg of CO2e)	642
USB upstream port type Number of USB Type-C upstream	USB Type-C	Total carbon emissions, standard deviation (kg of CO2e)	151
ports quantity USB Type-A downstream ports	1	Carbon emissions, manufacturing	333
quantity	5	(kg of CO2e) Carbon emissions, logistics (kg of	
USB Power Delivery up to	90 W	CO2e)	86
HDMI * HDMI ports quantity	1	Carbon emissions, energy usage (kg of CO2e)	217
HDMI version	1.4	Carbon emissions, end-of-life (kg of	5
DisplayPorts quantity	2	CO2e)	5
DisplayPort version	1.4	Total carbon emissions, w/o use	425
Headphone out *	×	phase (kg of CO2e) PAIA version	1.3.0
Charging port type	USB Type-C		1.3.0
Network		Other features	
Wi-Fi	×	Heavy metals free	Hg (mercury)
Ergonomics		Ethernet LAN (RJ-45) ports	1
VESA mounting *	1	Logistics data	
Panel mounting interface	100 x 100 mm	Harmonized System (HS) code	85285210
Cable lock slot *	✓		
Height adjustment *	1		
Height adjustment	15 cm		
Pivot	V		
Pivot angle	90 - 90°		
Swivelling	✓		















Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.