





# 3D expansion to break through limits

Unlike planar NAND memory, 3D NAND flash features memory cells stacked vertically in multiple layers. 3D NAND overcomes density limitations of 2D planar NAND, and delivers a higher level of performance and endurance.



# Performance boost for everyday computing

Taking full advantage of the SATA III 6Gb/s interface and built-in SLC caching technology, Transcend's SSD230S achieves exceptional transfer speeds of up to 560MB/s read and 520MB/s write.



# Guaranteed endurance and reliability

Transcend's SSD230S offers great
Terabytes Written (TBW) values (up to
1,120 TB) indicating the total amount of
data you can write into the drive over its
lifetime. It also features RAID engine and
LDPC coding, Garbage Collection,
Wear-leveling, and DevSleep.





#### 2.5" Solid State Drive

# SATA III 6Gb/s SSD230S

#### **Features**

- · Up to 560 MB/s read; 520 MB/s write
- 3D NAND flash memory and DDR3 DRAM cache
- Engineered with a RAID engine and LDPC (Low-Density Parity Check) coding to ensure data integrity; built-in SLC caching technology for exceptional transfer speeds
- Supports DevSleep ultra low power state,
   S.M.A.R.T., TRIM, and NCQ commands
- Download the SSD Scope software from Transcend's official website

# Transcend

## SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

## Specification

Appearanc	E
-----------	---

Capacity

Dimensions 100 mm x 69.85 mm x 6.8 mm (3.94" x 2.75" x 0.28")		
Weight	53 g (1.87 oz)	
Storage		
Flash Type	3D NAND flash	

128GB / 256GB / 512GB / 1TB / 2TB

## **Operating Environment**

Operating Temperature	0°C (32°F) ~ 70°C (158°F)
Operating Voltage	5V±5%

### Performance

Sequential Read/Write (CrystalDiskMark)	Read: 560 MB/s Write: 520 MB/s
4K Random Read/Write (IOmeter)	Read: 85,000 IOPS Write: 89,000 IOPS
Mean Time Between Failures (MTBF)	2,000,000 hour(s)
Terabytes Written (TBW)	1,120 TB
Drive Writes Per Day (DWPD)	0.3 (5 yrs)
Note	Speed may vary due to host hardware, software, usage, and storage capacity.
Warranty	
Certificate	CE/FCC/BSMI/KC/RCM
Warranty	Five-year Limited Warranty

## Ordering Information

128GB	TS128GSSD230S	
256GB	TS256GSSD230S	
512GB	TS512GSSD230S	
1TB	TS1TSSD230S	
2TB	TS2TSSD230S	

Product specifications are subject to change without notice. Pictures shown may differ from actual products. When used as a storage capacity unit, one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.



# 2.5" SSD Comparison









	SATA III 6Gb/s SSD220Q	SATA III 6Gb/s SSD230S	SATA III 6Gb/s SSD220S	SATA III 6Gb/s SSD370S
appearance				
Dimensions		100 mm x 69.85 mm x	6.8 mm (3.94" x 2.75" x 0.2	28")
Veight	45 g (1.59 oz)	53 g (1.87 oz)	45 g (1.59 oz)	57 g (2.01 oz)
torage				
lash Type	QLC NAND flash	3D NAND flash	3D NAND flash	MLC NAND flash
Capacity	500GB / 1TB	128GB ~ 2TB	120GB ~ 960GB	32GB ~ 1TB
Operating Environment				
Operating Temperature		0°C (32°F	) ~ 70°C (158°F)	
Performance				
Sequential Read/Write CrystalDiskMark)	550 MB/s 500 MB/s	560 MB/s 520 MB/s	550 MB/s 500 MB/s	530 MB/s 460 MB/s
4K Random Read/Write IOmeter)	57,000 IOPS 59,000 IOPS	85,000 IOPS 89,000 IOPS	65,000 IOPS 75,000 IOPS	75,000 IOPS 75,000 IOPS
Mean Time Between Failures MTBF)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)	2,000,000 hour(s)
Terabytes Written (TBW)	200 TB	1,120 TB	320 TB	2,940 TB
Orive Writes Per Day (DWPD)	0.19 (3 yrs)	0.3 (5 yrs)	0.3 (3 yrs)	2.5 (3 yrs)
Warranty				
Warranty	Three-year Limited Warranty	Five-year Limited Warranty	Three-year Limited Warranty	Three-year Limited Warranty
Technology				
TRIM & NCQ Command	<b>✓</b>	✓	<b>✓</b>	<b>✓</b>
S.M.A.R.T.	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
DDR3 DRAM Cache	-	<b>✓</b>	-	<b>✓</b>
	<b>✓</b>	✓	✓	✓
Advanced Garbage Collection	<u> </u>	<u>*</u>		
Advanced Garbage Collection DevSleep Mode	~ ~	·	<b>✓</b>	<b>✓</b>
			✓ ✓	-

<sup>\*</sup>Speed may vary due to host hardware, software, usage, and storage capacity.