

Product data sheet

Specifications



Actassi 19-DC Patching Frame Overhead 19" 4U

VDIM33174

Main

Range of product	Actassi
Product or component type	19" uprights
Device application	Overhead patching
Number of units 19" - Height	4U - 350 mm
Installation mode	Cable ladder mounted Tray mounted Overhead
Applications	To mount 19" equipment
Enclosure type	Open frame
Colour	Uprights: raven black

Complementary

Device composition	2 x 19" uprights
Load rating	15 kg static
Support equipment	2 x 19" uprights (vertical) 4 x mounting bracket (angled) 4 x bolts and nuts 4 x cord self-lock grip strip 2 x cord manager 1 x label holder
Material	Steel
Surface finish	Epoxy-polyester powder
Width	500 mm
Depth	160 mm

Environment

Standards	EIA-310D IEC 60297-3-100
-----------	-----------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.802 kg
Package 1 Height	9.0 cm

Package 1 width	26.0 cm
Package 1 Length	54.0 cm
Unit Type of Package 2	P12
Number of Units in Package 2	16
Package 2 Weight	59.896 kg
Package 2 Height	50.0 cm
Package 2 width	80.0 cm
Package 2 Length	120.0 cm
Unit Type of Package 3	S04
Number of Units in Package 3	4
Package 3 Weight	11.695 kg
Package 3 Height	30.0 cm
Package 3 width	40.0 cm
Package 3 Length	60.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------