

# Delock Displayport 1.2 Splitter 1 x mini Displayport in > 2 x HDMI out 4K

## Description

This splitter by Delock receives a Displayport signal from your PC or laptop and splits it to two connected displays. Thereby one mini Displayport connection can be used to operate two HDMI monitors.



## Specification

- Connector:  
Input: 1 x mini Displayport 20 pin male  
Output: 2 x HDMI-A 19 pin female
- Chipset: STDP4320
- Displayport 1.2a and High Speed HDMI specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Maximum resolution (depending on the system and the connected hardware):  
Displayport 1.1 or 1.2 Single Stream Transport (SST):  
up to 1920 x 1080 @ 60 Hz (mirror)
- Displayport 1.2 Multi Stream Transport (MST):  
up to 3840 x 2160 @ 30 Hz (mirror or extended)
- Supports 3D displays
- Supports HDCP 1.3
- Supports Eyefinity / Single Large Surface (SLS)
- Audio input formats: 7.1 channel up to 192 kHz sample rate
- Cable length: ca. 30 cm (without connector)
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 100 x 67 x 23 mm
- OS independent, no driver installation necessary

## System requirements

- A free mini Displayport female port

## Package content

- Mini Displayport Splitter

## Item No. 87696


EAN: 4043619876969

Country of origin: Taiwan, Republic of China

Package: Retail Box



## Images



<b>General</b>	
Specification:	Displayport 1.2a High Speed HDMI
<b>Interface</b>	
Input:	1 x mini Displayport 20 pin male
Output:	2 x HDMI-A 19 pin female
<b>Technical characteristics</b>	
Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz
<b>Physical characteristics</b>	
Housing:	metal
Cable length incl. connector:	30 cm
Colour:	black
Length:	100 mm
Width:	67 mm
Height:	23 mm