## **Product data sheet**

Specifications



# NetBotz 125kHz Rack Access Control

NBACS125

Overviev	١
----------	---

Presentation	Network appliances enabling remote and local access control for your NetShelter SX enclosures.
Lead time	Usually in Stock

#### Main

Man	
Number of rack unit	1U
Communication port protocol	A-Link SNMP
Provided Equipment	Cable ties Door sensor Installation guide Lock handles Proximity Card Proximity reader Rack Mounting brackets User Manual
Product Compatibility	Rack Sensor Pod 150

#### General

External Sensor Connection Type	Alarm Beacon 1 Modbus Output (RS-485) 1 Relay Output 1
APC Universal Sensors Supported	Door contact Dry Contact Humidity Smoke Fluid Spot Leak Temperature Vibration
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	6
Sensor Temperature Range	1550 °C +/- 1 °C 32122 °F +/- 1.8 °F

### **Physical**

Width	17.01 in (43.2 cm)	
Depth	2.32 in (5.9 cm)	
Net Weight	2.80 lb(US) (1.27 kg)	

Mounting preference	No preference
Mounting Mode	Rack-mounted
Environmental	
Ambient Air Temperature for Operation	32113 °F (045 °C)
Operating altitude	010000 ft
Relative Humidity	095 %
Ambient Air Temperature for Storage	5149 °F (-1565 °C)
Storage altitude	050000 ft (0.0015240.00 m)
Storage Relative Humidity	095 %
Ordering and shipping of	letails
GTIN	3606481978011
Package weight(Lbs)	5.40 lb(US) (2.45 kg)
Packing Units	

Package 1 Height

Package 1 width

Package 1 Length

Offer Sustainability	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

7.63 in (19.37 cm)

35.59 in (90.4 cm)

20.83 in (52.9 cm)